

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the East Boundary of T. 21 S., R. 8 W.

CHAINS

3.97 Branch, 2 lks. wide, course S. 25° W.; asc. 570 ft. over SE. slope, changing to S. slope.

32.70 Ridge, bears S. 80° E. and S. 70° W.; desc. 200 ft. over general N. slope.

38.00 Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 21 S
R 8 W R 7 W
S 1 S 6
S 12 S 7
1954

from which

A fir, 22 ins. diam., bears N. 11° E., 12 lks. dist., marked T21S R7W S6 BT.

A fir, 27 ins. diam., bears S. 1½° E., 34 lks. dist., marked T21S R7W S7 BT.

A fir, 18 ins. diam., bears S. 5° W., 11 lks. dist., marked T21S R8W S12 BT.

A fir, 25 ins. diam., bears N. 56½° W., 69 lks. dist., marked T21S R8W S1 BT.

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, and dogwood. Undergrowth, vine maple, huckleberry, hazel, and arrowwood.

N. 4° 13' E., bet. secs. 1 and 6.

Descend 500 ft. over steep, broken N. slope, through heavy timber and dense undergrowth.

10.00 Smith River, 50 lks. wide, course W.; asc. 70 ft. over rolling benchland.

38.00 The ¼ sec. cor. of secs. 1 and 6, determined from the remaining original bearing tree, as follows:

A solid fir snag, 26 ins. diam., bears S. 55° W., 41 lks. dist., with blaze healed; I open blaze and uncover scribe marks ¼ S.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼
S 1 S 6
1954

from which new bearing trees,

A fir, 30 ins. diam., bears N. 77° E., 38 lks. dist., marked ¼ S6 BT.