

## County Surveyor's Record, Douglas County, Oregon

15

## Dependent Resurvey of the East Boundary of T. 21 S., R. 8 W.

CHAINS

A fir, 23 ins. diam., bears S.  $26\frac{1}{4}^{\circ}$  W., 47 lks. dist.,  
marked  $\frac{1}{4}$  S1 BT.

N.  $1^{\circ} 46'$  E., beginning new measurement.

Ascend 20 ft. over gentle S. slope.

- 5.50 Indistinct back of flat spur, slopes SW.; desc. 60 ft. along W. slope.
- 16.20 Clabber Creek, 15 lks. wide, course S.  $20^{\circ}$  W.; asc. 25 ft. along E. slope near creek.
- 36.60 Clabber Creek, 10 lks. wide, course S.  $5^{\circ}$  E.; asc. 3 ft. along creek.
- 39.10 Leave creek, 10 lks. wide, course S.  $2^{\circ}$  W. at bend from N.  $50^{\circ}$  W.; asc. 20 ft. over SW. slope.
- 40.61 The cor. of Tps. 20 and 21 S., R. 8 W., on the W. bdy. of sec. 6, T. 21 S., R. 7 W., monumented with an iron post, 3 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Land, mountainous and gently rolling. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, and alder. Undergrowth, vine maple, huckleberry, hazel, arrowwood, poison oak, and salal.

Dependent Resurvey of a Portion of the Subdivisional Lines of  
T. 21 S., R. 8 W.  
(Restoring the 1883 survey by William P. Wright)


From the cor. of secs. 35 and 36, on the S. bdy. of the Tp.

N.  $2^{\circ} 53'$  W., bet. secs. 35 and 36.

Descend 307 ft. over NE. slope, through heavy timber and dense undergrowth.

- 10.10 A small spring, course E.; desc. gradually along slightly broken E. slope.
- 22.00 Ravine, drains SE.; asc. 196 ft. along broken SE. slope.
- 34.50 Spur, slopes N.  $70^{\circ}$  E.; desc. 270 ft. over broken N. slope.
- 38.55 Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap marked



from which

A fir, 35 ins. diam., bears S.  $33^{\circ}$  E., 30 lks. dist.,  
marked  $\frac{1}{4}$  S36 BT.

A fir, 62 ins. diam., bears S.  $12\frac{1}{4}^{\circ}$  W., 23 lks. dist.,  
marked  $\frac{1}{4}$  S35 BT.

Descend 354 ft. over very steep and broken NE. slope.