

County Surveyor's Record, Douglas County, Oregon


Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 8 W.

CHAINS

34.80 Ridge and tractor trail, bears NW. and SE.; desc. 103 ft. along steep E. slope.

37.15 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap marked



from which

A fir, 62 ins. diam., bears N. $62\frac{1}{4}^\circ$ E., 38 lks. dist., marked $\frac{1}{4}$ S25 BT.

A fir, 52 ins. diam., bears N. $80\frac{1}{4}^\circ$ W., 85 lks. dist., marked $\frac{1}{4}$ S26 BT.

Descend 33 ft. over E. slope.

45.10 Ravine, drains E.; asc. 55 ft. along broken E. slope.

47.40 Spur, slopes E.; desc. 23 ft. along rocky E. slope.

51.40 Ravine, course SE.; asc. 270 ft. over steep S. slope.

61.60 Spur, slopes NE.; bend in ridge and tractor trail, bears W., 1 ch. distant; desc. 270 ft. over steep NE. slope.


74.30 The point for the cor. of secs. 23, 24, 25, and 26, determined from the former positions of the original NE. and NW. bearing trees, both of which have fallen and slid some 3 chs. northeastward, and which were identified by the original scribe marks:

A stump hole, bears N. 10° E., 53 lks. dist.

A stump hole, bears N. 8° W., 26 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with brass cap marked



from which

A fir, 25 ins. diam., bears N. $40\frac{1}{4}^\circ$ E., 172 lks. dist., marked T21S R8W S24 BT.

A fir, 32 ins. diam., bears S. $49\frac{1}{2}^\circ$ E., 95 lks. dist., marked T21S R8W S25 BT.

A fir, 53 ins. diam., bears S. $35\frac{1}{2}^\circ$ W., 93 lks. dist., marked T21S R8W S26 BT.

A fir, 42 ins. diam., bears N. $31\frac{1}{4}^\circ$ W., 224 lks. dist., marked T21S R8W S23 BT.