

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 8 W.

CHAINS	
4.00	Dry bed of stream, 4 lks. wide, course N. 70° W. thence over level ground.
4.75	Branch, 4 lks. wide, course E. on bend to N.; asc. 25 ft. along broken E. slope.
18.80	Branch, 3 lks. wide, course S. 65° E.; asc. 65 ft. over S. slope.
22.20	Spur, slopes S. 30° E., asc. 190 ft. over broken SE. slope.
29.50	Spur, slopes S. 40° E.; asc. 75 ft. along E. slope.
36.05	Ravine, course SE.; asc. 120 ft. over S. slope.
38.58	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ \\ \text{S 11} \text{S 12} \\ \\ 1954 \end{array}$
	from which
	A fir, 10 ins. diam., bears S. 81 $\frac{1}{2}$ ° E., 37 lks. dist., marked $\frac{1}{4}$ S12 BT.
	A fir, 8 ins. diam., bears N. 34° W., 46 lks. dist., marked $\frac{1}{4}$ S11 BT.
	Ascend 200 ft. over precipitous S. slope, changing to SE. slope.
43.60	Spur, slopes S. 80° E.; desc. 50 ft. over NE. slope.
45.90	Ravine, course E.; asc. 200 ft. over SE. slope.
52.10	Spur ridge, bears E. and W.; desc. 260 ft. over N. slope.
57.50	Branch, 1 lk. wide, course N. 70° E.; asc. 100 ft. over SE. slope.
61.90	Spur ridge, bears N. 60° E. and S. 60° W.; desc. 250 ft. over N. slope.
66.65	Branch, 1 lk. wide, course N. 75° E.; asc. 100 ft. over SE. slope.
73.00	Ridge, bears N. 40° E. and S. 40° W.; desc. 150 ft. over NW. slope.
77.16	The cor. of secs. 1, 2, 11, and 12, determined from the remaining original bearing tree, as follows: A fir and cedar, grown together, 50 ins. diam., bears S. 71° W., 95 lks. dist., with blaze nearly healed. I open and uncover scribe marks S11 BT T21S R under 71 years overgrowth. (Wright calls for a fir, but the marks are actually in the cedar wood of the composite tree.)
	At the corner point
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, and in a small mound of stone to top, with brass cap marked

T 21 S R 8 W
 $\frac{\text{S 2} | \text{S 1}}{\text{S 11} | \text{S 12}}$
 1954