

## County Surveyor's Record, Douglas County, Oregon

35

## Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 8 W.

## CHAINS

N. 88° 51' W., bet. secs. 14 and 23.

Ascend 100 ft. over SE. slope, through scattering timber, partly burned; undergrowth nearly all consumed.

2.70 Top of steep ascent on S. slope; desc. 30 ft. along rolling S. slope.

19.35 Branch, 2 lks. wide, course S. 20° E.; asc. 30 ft. along rolling S. slope.

24.00 Branch, 1 lk. wide, course S. 40° E.; asc. 120 ft. along rolling S. slope, changing to SE. slope.

37.43 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 14 \\ S 23 \end{array}$$
 1954

from which

A fir, 15 ins. diam., bears N. 44° E., 48 lks. dist., marked  $\frac{1}{4}$  S14 BT.A fir, 50 ins. diam., bears S. 53 $\frac{1}{2}$ ° W., 55 lks. dist., marked  $\frac{1}{4}$  S23 BT.

Ascend 300 ft. over SE. slope, changing to steep E. slope.

42.50 Enter total burn area; edge bears N. and SE.

46.46 Top of high hill in divide bet. Umpqua River and Smith River; divide bears N. 60° E. and S. 30° E.; spur ridge, slopes NW.; an impassable tractor trail, bears N. 60° E. and NW.; desc. 710 ft. over steep, broken SW. slope.

74.86 The cor. of secs. 14, 15, 22, and 23.

Land, rolling in E.  $\frac{1}{2}$  mi.; mountainous in W.  $\frac{1}{2}$  mi. Soil, sandy clay loam, mostly fine, burned shale in W.  $\frac{1}{2}$  mi. Timber, scattering fir, hemlock, and cedar in E.  $\frac{1}{2}$  mi.; W.  $\frac{1}{2}$  mi., none. Undergrowth, mostly low salal; other brush burned and not yet growing.

N. 89° 01' W., bet. secs. 15 and 22.

Descend 175 ft. over SW. slope, through burned area.

6.80 Branch, 3 lks. wide, course S. 30° W.; asc. 30 ft. along broken S. slope.

15.20 Branch, 2 lks. wide, course S.; asc. 100 ft. along broken S. slope.

23.80 Spur, slopes S. 20° W.; desc. 100 ft. over SW. slope.

30.63 Unimproved logging road, bears N. and S.

37.47 Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 15 \\ S 22 \end{array}$$
 1954