

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 8 W.

CHAINS

from which

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears N. 20° W., 50 lks. dist., with brass cap marked $\frac{1}{4}$ S15 RM 1954 and an arrow pointing to the corner.

An iron post, 3 ft. long, 1 in. diam., set 28 ins. in the ground, for a reference monument, bears S. 20° E., 50 lks. dist., with brass cap marked $\frac{1}{4}$ S22 RM 1954 and an arrow pointing to the corner.

Descend 160 ft. over SW. slope.

- 43.20 Gravelled logging road, 40 lks. wide, bears NW. and SE.
- 44.10 Creek, 8 lks. wide, course NW.; asc. 10 ft. along N. slope.
- 45.60 Bed of dry stream, 2 lks. wide, course N. 10° E.; asc. 140 ft. over NE. slope.
- 50.60 Spur, slopes N.; desc. 80 ft. over NW. slope.
- 52.80 Bed of dry stream, 2 lks. wide, course N.; asc. 180 ft. over NE. slope.
- 56.60 Spur, slopes N. 10° E.; asc. 70 ft. along broken N. slope.
- 61.40 Spur ridge, bears N. and S.; desc. 340 ft. over W. slope.
- 70.70 East Fork of Mometown Creek, 8 lks. wide, course N. 25° E.; asc. 105 ft. over SE. slope.
- 71.40 Unimproved logging road, bears N. 25° E. and S. 10° W.
- 74.94 The cor. of secs. 15, 16, 21, and 22, described by Norman D. Price in the field notes of the dependent resurvey of the W. half of T. 21 S., R. 8 W., in 1945, as a hemlock stump, has been destroyed by fire, and only the remains of the roots are found.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 21 S R 8 W	
S 16	S 15
S 21	S 22
1954	

from which

An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 38° E., 50 lks. dist., with brass cap marked T21S R8W S22 RM 1954 and an arrow pointing to the corner.

An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 38° W., 50 lks. dist., with brass cap marked T21S R8W S16 RM 1954 and an arrow pointing to the corner.

From the corner point, the witness cor. to the cor. of secs. 15, 16, 21, and 22, set by Price in 1945, bears N. 0° 50' E., 10 lks. dist., monumented with an iron post, 2 ins. diam., 20 ins. above ground, firmly set, with brass cap marked

T 21 S R 8 W	
W C	
S 16	S 15
S 21	S 22
1945	