

County Surveyor's Record, Douglas County, Oregon

38

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 8 W.

CHAINS

73.88

The cor. of secs. 10, 11, 14, and 15, determined at record bearing and distance from the remaining original bearing trees, as follows:

A fir, 40 ins. diam., bears N. 29° E., 39 lks. dist., with illegible scribe marks visible on burned face of blaze.

A hemlock, 22 ins. diam., bears S. 50° W., 10 lks. dist., with partial scribe marks visible on opened blaze.

A fir stump, 18 ins. diam., bears N. 33° W., 23 lks. dist., with blaze rotted away.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with brass cap marked

T 21	S R	8 W
S 10	S 11	
S 15	S 14	
1952		

from which new bearing trees,

A cedar, 19 ins. diam., bears N. 56½° E., 76 lks. dist., marked T21S R8W S11 BT.

A hemlock, 21 ins. diam., bears S. 54½° E., 49 lks. dist., marked T21S R8W S14 BT.

A fir, 48 ins. diam., bears S. 35° W., 128 lks. dist., marked T21S R8W S15 BT.

A fir, 45 ins. diam., bears N. 23° W., 73 lks. dist., marked T21S R8W S10 BT.

Land, mountainous. Soil, sandy shale, overlying sandstone. Timber, fir, hemlock, cedar, maple, chinquapin, and madrona in unburned portion. Undergrowth, some vine maple, hazel, salal, huckleberry, salmonberry, and poison oak in N. portion; brush just beginning to come back in burn.

From the cor. of secs. 11, 12, 13, and 14.

S. 88° 45' W., bet. secs. 11 and 14.

Ascend 25 ft. over NE. slope, through heavy timber and dense undergrowth.

1.25 Point of spur, slopes N.; desc. 90 ft. over NW. slope.

7.60 Branch, 5 lks. wide, course N. 60° E.; asc. 110 ft. over SE. slope.

18.90 Spur, slopes S.; desc. 50 ft. over SW. slope.

24.60 Branch, 5 lks. wide, course S. 60° E.; asc. 480 ft. over NE. slope.

36.40 Spur, slopes N. 20° E.; desc. 65 ft. along broken N. slope.

40.21 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked