

County Surveyor's Record, Douglas County, Oregon

43

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 8 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to solid rock, and in a small mound of stone to top, with brass cap marked

$$\frac{1}{4} \frac{S \ 2}{S \ 11}$$

1954

from which new bearing trees,

A hemlock, 10 ins. diam., bears S. $77\frac{1}{2}^{\circ}$ E., 6 lks. dist., marked $\frac{1}{4}$ S11 BT.

A fir, 25 ins. diam., bears N. $48\frac{1}{2}^{\circ}$ W., 45 lks. dist., marked $\frac{1}{4}$ S2 BT.

N. $89^{\circ} 22'$ W., beginning new measurement.

Ascend 14 ft. along N. slope.

1.30 Top of ascent on N. slope; desc. 158 ft. over NW. slope.

9.03 Left bank of Smith River, course S. 50° W.

10.93 Right bank of Smith River; asc. 8 ft. over bottom land.

14.25 Gravelled road, 35 lks. wide, bears N. 57° E. and S. 57° W.

15.35 Branch, 4 lks. wide, course S.; asc. 20 ft. over bottom land.

19.50 Branch, 3 lks. wide, course S. 10° E.; asc. 86 ft. over SE. slope, changing to S. slope.

28.85 Wet ravine, course S. 15° E.; continue along broken S. slope.

32.40 Branch, 2 lks. wide, course S. 20° E.; asc. 27 ft. along broken S. slope.

34.90 Spring branch, 1 lk. wide, course S. 10° E.; asc. 127 ft. over SE. slope, changing to S. slope.

40.45 The cor. of secs. 2, 3, 10, and 11.

Land, mountainous except for narrow strip along right bank of river. Soil, sandy clay loam. Timber, fir, hemlock, cedar, yew, maple, alder, madrona, chinquapin, and dogwood. Undergrowth, vine maple, huckleberry, salmonberry, hazel, and salal.

S. $89^{\circ} 51'$ W., bet. secs. 3 and 10.

Ascend 18 ft. along S. slope, through heavy timber and dense undergrowth.

3.75 Wet ravine, course SE.; asc. 55 ft. over broken SE. slope.

9.20 High spur, slopes S. 20° W.; desc. 367 ft. over W. slope.

17.10 Gravelled road, 30 lks. wide, bears N. and S.

17.50 Right bank of Smith River, course N. 30° W.

19.30 Left bank of Smith River; asc. 100 ft. over gradual E. slope.

33.82 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked