

County Surveyor's Record, Douglas County, Oregon  
4

Dependent Resurvey of Portion of W. Bdy., Sec. 31, T. 24 S., R. 3 W.

CHAINS

from which

A fir, 11 ins. diam., bears N.  $25\frac{1}{2}^{\circ}$  E., 23 lks. dist.,  
mkd. N 1/16 S31 BT.

A fir, 18 ins. diam., bears S.  $14^{\circ}$  W., 8 lks. dist.,  
mkd. N 1/16 S36 BT.

Ascend 431 ft. over broken S. slope, leave logged area, edge bears  
E. and W.; enter heavy timber and scattering undergrowth.

36.45 Woven-wire fence, bears N.  $10^{\circ}$  W. and S.  $10^{\circ}$  E., curving slightly S.

37.90 Spur ridge, bears NW. and S.  $50^{\circ}$  E.; desc. 27 ft. over NE. slope.

39.34 The cor. of secs. 25, 30, 31, and 36, perpetuated by N. D. Price,  
in 1950, from original bearing trees and monumented with an iron  
post, 2 ins. diam., 1 in. above ground, firmly set, with brass cap  
mkd.

|        |       |
|--------|-------|
| T 24 S |       |
| R 4 W  | R 3 W |
| S 25   | S 30  |
| S 36   | S 31  |
| 1950   |       |

from which original bearing trees:

A sawed fir stump, 55 ins. diam., bears N.  $61^{\circ}$  E., 10 lks.  
dist., no scribe marks visible.

A fir, 27 ins. diam., bears S.  $77^{\circ}$  E., 15 lks. dist.,  
with healed blaze.

A sawed fir stump, 31 ins. diam., bears S.  $20^{\circ}$  W., 55 lks.  
dist., no scribe marks visible.

and bearing tree by Price in 1950:

A fir turnout, 11 ins. diam., bears N.  $51^{\circ}$  W., 15 lks. dist.,  
with healed blaze.

and new bearing trees:

A fir, 20 ins. diam., bears N.  $55^{\circ}$  E., 75 lks. dist.,  
mkd. T24S R3W S30 BT.

A fir, 20 ins. diam., bears S.  $23\frac{1}{2}^{\circ}$  W., 74 lks. dist.,  
mkd. T24S R4W S36 BT.

A fir, 10 ins. diam., bears N.  $50\frac{1}{2}^{\circ}$  W.,  $36\frac{1}{2}$  lks. dist.,  
mkd. T24S R4W S25 BT.

Land, mountainous. Soil, clay loam and rocky. Timber, fir, cedar,  
madrone, dogwood, and maple; undergrowth, vine maple, hazel, arrow-  
wood, blackberry and fern.

Dependent Resurvey of the E. and N. Bdy. of Sec. 31,  
T. 24 S., R. 3 W.  
(Restoring the 1872 survey by W. H. Byars)

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.

N.  $0^{\circ}28'$  E., bet. secs. 31 and 32, marking and blazing the true  
line.

Descend 207 ft. over NE. slope, through old logged area, second  
growth timber, reproduction and dense undergrowth.