

County Surveyor's Record, Douglas County, Oregon
5

Dependent Resurvey of the E. and N. Bdy. of Sec. 31, T. 24 S., R. 3 W.

CHAINS 6.34	Hinkle Creek, 20 lks. wide, course NW.; asc. 209 ft. over SW. slope.
9.10	Leave timber, edge bears NW. and SE.; enter open field.
9.50	Woven-wire fence, bears N. 20° E. and S. 20° W.
12.10	Woven-wire fence, bears NW. and SE.; leave field, edge bears NW. and SE.
12.70	Maintained, gravel surfaced road, bears NW. and SE.; enter heavy timber, edge bears NW. and SE.
20.54	Point for the S 1/16 sec. cor. of secs. 31 and 32. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S 1/16 S 31 S 32 1958 </div> from which A fir, 13 ins. diam., bears N. 79¾° E., 35 lks. dist., mkd. S 1/16 S32 BT. A fir, 6 ins. diam., bears N. 65½° W., 48 lks. dist., mkd. S 1/16 S31 BT. Ascend 135 ft. over SW. slope.
27.27	Spur, slopes W.; desc. 319 ft. over NW. slope.
32.00	Leave heavy timber, edge bears NE. and SW.; enter old logged area and scattered timber.
33.15	Maintained, gravel surfaced access road, bears E. and W.
36.57	Railroad track of the Weyerhaeuser Lumber Company, bears NE. and SW.; enter bottom land, edge bears NE. and SW.
36.97	Two strand telephone line, bears NE. and SW.
41.08	The ¼ sec. cor. of secs. 31 and 32, perpetuated and recorded by F. C. Frear, County Surveyor, in 1938, at record bearing and distance from evidence of one of the original maple bearing trees, which is no longer in existence, monumented by an iron pipe, 1½ ins. diam., firmly set, 1 in. above ground. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 24 S R 3 W S 31 S 32 1958 </div> from which bearing tree by J. W. Byron, County Surveyor, in 1954: A fir, 12 ins. diam., bears S. 30° W., 69½ lks. dist., mkd. ¼ S31 BT. and new bearing tree: