

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the E. and N. Bdy. of Sec. 31, T. 24 S., R. 3 W.

CHAINS

A cedar, 23 ins. diam., bears S. $68\frac{3}{4}^{\circ}$ E., 9 lks. dist.,
mkd. $\frac{1}{4}$ S32 BT.

Reset the iron pipe alongside the iron post.

N. $1^{\circ}07'$ E., beginning new measurement.

Ascend 4 ft. over S. slope, through cultivated field.

- 4.01 Woven-wire fence, bears E. and W.
- 4.53 From this point the SW. cor. of a wood frame dwelling bears W.,
57 lks. dist.
- 5.81 Top of ascent, slopes NW.; desc. 11 ft. over NW. slope.
- 8.04 Calapooya Creek, 80 lks. wide, course SW.; asc. 339 ft. over S.
slope.
- 11.91 Maintained, gravel surfaced access road, 30 lks. wide, bears NE.
and SW.
- 13.74 Enter logged area, edge bears NE. and SW.; through scattering
timber, dense undergrowth and reproduction.
- 20.865 Point for the N 1/16 sec. cor. of secs. 31 and 32.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the
ground, with brass cap mkd.
- | | | |
|------|--------|------|
| | N 1/16 | |
| | | |
| S 31 | | S 32 |
| | | |
| | 1958 | |
- from which
- A fir, 5 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ E., 13 lks. dist.,
mkd. N 1/16 S32 BT.
- A fir, 6 ins. diam., bears N. $89\frac{1}{4}^{\circ}$ W., 37 lks. dist.,
mkd. N 1/16 S31 BT.
- Ascend 315 ft. over S. slope.
- 29.88 Enter heavy timber, edge bears E. and W.
- 31.38 Spur, slopes E.; desc. 180 ft. over NE. slope.
- 41.73 The cor. of secs. 29, 30, 31, and 32, monumented and recorded by J.
W. Byron, County Surveyor, in 1956, at record distance from the
original bearing trees, with an iron post, 1 in. diam., firmly set
12 ins. above ground, with brass cap mkd. T24S R3W SEC COR 29 30
31 32 1956.
- from which original bearing trees:
- A sawed fir stump, 65 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ E., 48 lks.
dist., with no scribe marks visible. (Record bearing,
N. 70° E.)
- A rotted hemlock turnout, 13 ins. diam., bears S. 45° W.,
20 lks. dist., with no scribe marks visible. (Record
bearing tree, a fir)
- A hemlock turnout, 26 ins. diam., bears N. 62° W., 30 lks.
dist., with no scribe marks visible. (Record bearing
tree, a fir)
- and bearing trees by J. W. Byron, County Surveyor, in 1956: