

County Surveyor's Record, Douglas County, Oregon

10

Subdivision of Sec. 31, T. 24 S., R. 3 W.

CHAINS
50.00

Spur, slopes E.; desc..96 ft. over N. slope, changing to NE. slope.

53.28


Ravine, drains E.; asc. 13 ft. over SE. slope.

56.72

Top of ascent, slopes E.; desc. 27 ft. over NE. slope.

61.37

Point for the center N 1/16 sec. cor. of sec. 31.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A fir, 10 ins. diam., bears S. $27\frac{1}{2}^{\circ}$ E., 45 lks. dist.,
mkd. CN 1/16 S31 BT.A fir, 30 ins. diam., bears N. $29\frac{1}{4}^{\circ}$ W., 39 lks. dist.,
mkd. CN 1/16 S31 BT.

Descend 240 ft. over NE. slope.

71.23

Draw, drains E.; asc. 57 ft. over SE. slope.

74.35

Spur, slopes NE.; desc. 91 ft. over N. slope.

77.73

Draw, drains NE.; asc. 11 ft. over SE. slope.

78.72

Spur, slopes E.; desc. 45 ft. over NE. slope.

81.66

The $\frac{1}{4}$ sec. cor. of secs. 30 and 31.From the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.N. $89^{\circ}45'$ W., along the E. and W. center line of sec. 31.Descend 23 ft. over gentle NW. slope, through open pasture land,
parallel to old rail fence.

6.28

From this point the SW. cor. of a wood frame dwelling, bears N.,
 $83\frac{1}{2}$ lks. dist.

7.51

From this point the NE. cor. of a wood frame dwelling, bears S.,
100 lks. dist.

9.00

Calapooya River, 40 lks. wide, course S. 35° W.; asc. 48 ft. over
SE. slope.

11.09

From this point the SW. cor. of a wood frame dwelling, bears N.,
 $37\frac{1}{2}$ lks. dist.

11.28

Top of ascent, slopes SW.; desc. 24 ft. over SW. slope.

12.85

Maintained, gravel surfaced road, bears NE. and SW.

13.70

Jeffers Creek, 6 lks. wide, course S.; enter scattering timber and
dense undergrowth; asc. 183 ft. over SE. slope.

19.56

Point for the center E 1/16 sec. cor. of sec. 31.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground to bedrock, and in a mound of stone, 2 ft. base, to top,
with brass cap mkd.