

## County Surveyor's Record, Douglas County, Oregon

## Remonumentation of Certain Original Corner Points, T. 24 S., R. 8 W.

CHAINS

A fir, 9 ins. diam., bears S.  $40\frac{1}{2}^{\circ}$  W., 60 lks. dist.,  
mkd. T25S R8W S1 BT.

An alder, 9 ins. diam., bears N.  $71^{\circ}$  W., 44 lks. dist.,  
mkd. T24S R8W S36 BT.

(Remonumenting corners established by H. L. Chandler in 1894)

The cor. of secs. 11, 12, 13, and 14, determined at record bearing  
and distance from the remaining original bearing trees:

A fir, 30 ins. diam., bears N.  $25^{\circ}$  E., 80 lks. dist.,  
mkd. with a healed blaze.

A fir, 40 ins. diam., bears S.  $10^{\circ}$  E., 76 lks. dist.,  
mkd. with a healed blaze.

A fir, 30 ins. diam., bears N.  $31^{\circ}$  W., 49 lks. dist.,  
mkd. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap mkd.

T 24 S R 8 W
S 11   S 12
S 14   S 13
1959

from which

A madrone, 10 ins. diam., bears N.  $56\frac{1}{2}^{\circ}$  E., 14 lks. dist.,  
mkd. T24S R8W S12 BT.

A white fir, 11 ins. diam., bears S.  $43^{\circ}$  E., 79 lks. dist.,  
mkd. T24S R8W S13 BT.

A white fir, 6 ins. diam., bears S.  $33\frac{1}{2}^{\circ}$  W., 42 lks. dist.,  
mkd. T24S R8W S14 BT.

A white fir, 37 ins. diam., bears N.  $55\frac{1}{2}^{\circ}$  W., 52 lks. dist.,  
mkd. T24S R8W S11 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, determined at record bearing  
and distance from the only remaining original bearing tree:

A dead fir, 65 ins. diam., bears South, 50 lks. dist.,  
bark scribed  $\frac{1}{4}$  S.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap mkd.

T 24 S R 8 W
$\frac{1}{4}$ S 12
S 13
1959

from which

A fir, 13 ins. diam., bears N.  $77\frac{1}{2}^{\circ}$  E., 20 lks. dist.,  
mkd.  $\frac{1}{4}$  S12 BT.