

## County Surveyor's Record, Douglas County, Oregon

## Remonumentation of Certain Original Corner Points, T. 24 S., R. 8 W.

CHAINS

A hemlock, 8 ins. diam., bears N. 17° W., 43 lks. dist.,  
mkd. T24S R8W S27 BT.

The cor. of secs. 22, 23, 26, and 27, determined at record distance  
from the remains of the original bearing trees:

A fir, 63 ins. diam., bears N. 55° E., 89 lks. dist.,  
with healed blaze.

A rotted fir stump, bears S. 20° E., 70 lks. dist.

A fir, 60 ins. diam., bears S. 34½° W., 109 lks. dist.,  
with a healed blaze. (Record bearing, S. 31° W.)

A rotted fir stump, bears N. 5° W., 60 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the  
ground, with brass cap mkd.

T 24 S R 8 W
S 22   S 23
S 27   S 26
1959

from which

A white fir, 8 ins. diam., bears N. 32° E., 19 lks. dist.,  
mkd. T24S R8W S23 BT.

A white fir, 7 ins. diam., bears S. 62½° E., 21 lks. dist.,  
mkd. T24S R8W S26 BT.

A white fir, 8 ins. diam., bears S. 32° W., 26 lks. dist.,  
mkd. T24S R8W S27 BT.

A white fir, 9 ins. diam., bears N. 34° W., 42 lks. dist.,  
mkd. T24S R8W S22 BT.

The cor. of secs. 21, 22, 27, and 28, determined at record bearing  
and distance from the original bearing trees:

A sawed fir stump, 35 ins. diam., bears N. 41° E., 63 lks.  
dist., with a healed blaze.

A fir, 38 ins. diam., bears S. 52½° E., 33 lks. dist.,  
with a healed blaze.

A rotted fir stump, 35 ins. diam., bears S. 37° W., 109 lks.  
dist., with illegible scribe marks visible on partially  
opened blaze.

A fir, 40 ins. diam., bears N. 4° W., 73 lks. dist.,  
with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground, with brass cap mkd.

T 24 S R 8 W
S 21   S 22
S 28   S 27
1959

from which