

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 24 S., R. 8 W.

CHAINS

A white fir, 7 ins. diam., bears N. 13° E., 36 lks. dist.,
mkd. T24S R8W S22 BT.

A white fir, 7 ins. diam., bears S. 16° E., 52 lks. dist.,
mkd. T24S R8W S27 BT.

A hemlock, 13 ins. diam., bears S. 33½° W., 83 lks. dist.,
mkd. T24S R8W S28 BT.

A white fir, 7 ins. diam., bears N. 18½° W., 41 lks. dist.,
mkd. T24S R8W S21 BT.

The cor. of secs. 8, 9, 16, and 17, determined at record bearing
and distance from the remains of the original bearing trees:

A stump hole, with roots of a fir tree, bears N. 52° E.,
31 lks. dist.

A fir snag, 28 ins. diam., bears S. 18½° E., 34 lks. dist.,
with a healed blaze.

A fir, 37 ins. diam., bears S. 57° W., 10 lks. dist.,
with a healed blaze.

A rotted fir stump, bears N. 31° W., 9 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd.

T 24	S R 8 W
S 8	S 9
S 17	S 16
1959	

from which

A fir, 20 ins. diam., bears N. 25° E., 54 lks. dist.,
mkd. T24S R8W S9 BT.

A fir, 42 ins. diam., bears S. 7° E., 185 lks. dist.,
mkd. T24S R8W S16 BT.

A fir, 34 ins. diam., bears S. 69½° W., 185 lks. dist.,
mkd. T24S R8W S17 BT.

A fir, 24 ins. diam., bears N. 29° W., 36 lks. dist.,
mkd. T24S R8W S8 BT.

The cor. of secs. 19, 20, 29, and 30, determined at record distance
from the remains of the original bearing trees:

A stump hole, with roots and bark of a fir tree, bears
N. 27° E., 69 lks. dist. (Record bearing, S. 27° E.)

A downed fir, 40 ins. diam., bears S. 13° E., 74 lks. dist.,
with scribe marks BT visible on partially opened blaze.

A fir, 60 ins. diam., bears S. 28° W., 25 lks. dist.,
with healed blaze.

A rotted fir stump, bears N. 23° W., 68 lks. dist.

At the corner point