

County Surveyor's Record, Douglas County, Oregon
2

Dependent Resurvey of a Portion of the E. Bdy., T. 24 S., R. 7 W.

CHAINS

T 24 S	
R 7 W	R 6 W
S 1	S 6
S 12	S 7
1957	

from which

A fir, 16 ins. diam., bears N. 72° E., 94 lks. dist.,
mkd. T24S R6W S6 BT.

A fir, 55 ins. diam., bears S. 89 $\frac{1}{4}$ ° E., 64 lks. dist.,
mkd. T24S R6W S7 BT.

A fir, 44 ins. diam., bears S. 89° W., 62 lks. dist.,
mkd. T24S R7W S12 BT.

A maple, 12 ins. diam., bears N. 53° W., 52 lks. dist.,
mkd. T24S R7W S1 BT.

N. 2°08' E., bet. secs. 1 and 6, marking and blazing the true line.

Descend 3 ft. over N. slope.

- 0.28 Gully, drains S. 80° E.; asc. 90 ft. over S. slope.
- 2.19 Spur, slopes SE.; asc. 342 ft. along E. slope.
- 28.66 Creek, 7 lks. wide, course S. 10° E.; asc. 311 ft. over SW. slope,
changing to S. slope.
- 39.525 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate
distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground,
with brass cap mkd.

T 24 S	
↑	
R 7 W	R 6 W
S 1	S 6
1957	

from which

A white fir, 15 ins. diam., bears S. 78° E., 52 lks. dist.,
mkd. $\frac{1}{4}$ S6 BT.

A fir, 12 ins. diam., bears S. 76° W., 88 lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

Ascend 333 ft. over S. slope.

- 54.64 Ridge, bears N. 65° W. and S. 65° E.; desc. 96 ft. over NE. slope.
- 59.00 Ravine, drains E.; asc. 49 ft. over SE. slope.
- 61.53 Spur, slopes E.; desc. 297 ft. over NE. slope.
- 70.17 Creek, 10 lks. wide, course S. 50° E.; asc. 291 ft. over S. slope.
- 79.05 The cor. of Tps. 23 and 24 S., Rs. 6 and 7 W., previously described
in the field notes of the dependent resurvey of S. bdy. of T. 23
S., R. 6 W., of this Group.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock and
cedar; undergrowth, salal, poison oak, vine maple and madrone.