

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS

A fir snag, 36 ins. diam., bears S.  $68\frac{1}{2}^{\circ}$  W., 37 lks. dist.,  
mkd. S with other marks not legible.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground,  
with brass cap mkd.

S 1	S 6
R6W	R5W
T23S	
S C	
1943	

from which

A fir, 9 ins. diam., bears S.  $29^{\circ}$  E., 103 lks. dist.,  
mkd. T23S R5W S6 SC BT.

A fir, 6 ins. diam., bears S.  $11^{\circ}$  W., 89 lks. dist.,  
mkd. T23S R6W S1 SC BT.

N.  $89^{\circ}40'$  W., along the N. bdy. of sec. 1, marking and blazing the  
true line.

Ascend 184 ft. over SE. slope, through heavy timber and dense  
undergrowth.

6.30 Fence, bears N. and S.; leave timber and dense undergrowth; enter  
S. edge of field, bears E. and W.

8.12 The closing cor. of Tps. 22 S., Rs. 5 and 6 W., determined at  
record bearing and distance from the only remaining bearing tree:

A fir, 48 ins. diam., bears N.  $51^{\circ}$  E., 71 lks. dist.,  
marks grown over.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground,  
with brass cap mkd.

C C	
T22S	
R6W	R5W
S36	S31
T23SR6W	
S 1	
1943	

from which

A fir, 20 ins. diam., bears N.  $56\frac{1}{2}^{\circ}$  W., 237 lks. dist.,  
mkd. T22S R6W S36 CC BT.

Over rolling land.

12.95 Fence, bears N. and S.; leave field, enter heavy timber, edge bears  
N. and S.; asc. 97 ft. over SE. slope.

17.22 Spur, slopes S.; along broken S. slope.

26.52 Head of ravine, course S.  $40^{\circ}$  E.; asc. 18 ft. over SE. slope.

32.00 Spur, slopes S.  $20^{\circ}$  E.; desc. 23 ft. over SW. slope.

33.75 Creek, 2 lks. wide, course SE.; asc. 7 ft. over S. slope.

37.69 The standard  $\frac{1}{4}$  sec. cor. of sec. 1, determined at record bearing  
and distance from the only remaining bearing tree: