

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS

A fir, 38 ins. diam., bears S. 68° E., 63 lks. dist.,
mkd. BT.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
with brass cap mkd.

1/4 S 1
S C
1943

from which

A fir, 20 ins. diam., bears S. 68° E., 106 lks. dist.,
mkd. 1/4 S1 SC BT.

A fir, 24 ins. diam., bears S. 65 1/2° W., 36 lks. dist.,
mkd. 1/4 S1 SC BT.

N. 89°28' W., beginning new measurement.

Ascend 193 ft. over SE. slope.

5.27 Spur, slopes SE.; desc. 23 ft. over SW. slope.

7.25 Ravine, course SE.; asc. 94 ft. over E. slope.

10.20 The 1/4 sec. cor. of sec. 36 only, T. 22 S., R. 6 W., determined at
record bearing and distance from the original bearing trees:

A fir, 48 ins. diam., bears N. 10° E., 3 lks. dist.,
mkd. 1/4 with other mks. grown over.

A laurel, partly dead, 20 ins. diam., bears N. 45° W.,
23 lks. dist., mks. rotted off.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
with brass cap mkd.

1/4 S 36
1943

from which

A fir, 12 ins. diam., bears N. 57° W., 102 lks. dist.,
mkd. 1/4 S36 BT.

Ascend 226 ft. over SE. slope.

42.17 The standard cor. of secs. 1 and 2, determined at record bearing
and distance from the only remaining original bearing tree:

A fir snag, 24 ins. diam., bears S. 40° E., 19 lks. dist.,
mkd. S1 SC T23S R6W BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
with brass cap mkd.

S 2 | S 1
T23SR6W
, S C
1943

from which