

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS
48.44

Point for the $\frac{1}{4}$ sec. cor. of sec. 35, T. 22 S., R. 6 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} S 35$$

1943

from which

A fir, 50 ins. diam., bears N. 48° E., 88 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A fir, 14 ins. diam., bears N. 76° W., 66 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

Descend 44 ft. over NW. slope.

54.10 Ravine, course N. 20° W.; asc. 28 ft. over NE. slope.

56.30 Small spur, slopes N.; desc. 79 ft. over NW. slope.

62.15 Creek, 6 lks. wide, course N.; asc. 200 ft. over NE. slope.

80.48 The standard cor. of secs. 2 and 3, determined at record bearing and distance from the original bearing trees:

A fir, 54 ins. diam., bears S. 24° E., 42 lks. dist., marks grown over.

A cedar, 22 ins. diam., bears S. 27° W., 72 lks. dist., marks grown over.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} S 3 | S 2 \\ T23SR6W \\ S C \\ 1943 \end{array}$$

*FD. B. C. 6/92
J. BRANCH
M115-26 & M115-23*

Land, mountainous. Soil, sandy and rocky clay. Timber, fir, hemlock, and cedar. Undergrowth, alder, poison oak, vine maple, laurel, rhododendron, and manzanita.

N. 88°00' W., along the N. bdy. of sec. 3.

Ascend 40 ft. over NE. slope, through heavy timber and dense undergrowth.

4.20 Spur, slopes N.; 15 ft. over NW. slope.

8.17 The closing cor. of secs. 34 and 35, T. 22 S., R. 6 W., determined at record bearing and distance from the original bearing trees:

A fir, 24 ins. diam., bears N. 26° E., 23 lks. dist., mkd. CC T22S R6W S35 BT.

A rotted fir stump, 30 ins. diam., bears N. 62° W., 38 lks. dist., no marks remaining.

At the corner point