

County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS
40.19

The standard cor. of secs. 3 and 4, monumented by a sandstone, 12 x 10 x 6 ins., firmly set, with 3 grooves on the east and 3 grooves on the west, and SC on the S. face.

from which

A fir, 32 ins. diam., bears S. 20° E., 20 lks. dist.,
mkd. T23S R6W S3 SC BT.

A fir, 48 ins. diam., bears S. 45° W., 18 lks. dist.,
mkd. with a healed blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
with brass cap mkd.

T22SR6W
S 34
S 4 | S 3
T23SR6W
S C
1943

*FD. B.C. 6/92
J. BRANCH
M115-26 &
M115-23*

Deposit stone alongside the iron post, properly oriented.

Land, mountainous. Soil, sandy and rocky clay. Timber, fir, hemlock, and cedar. Undergrowth, salal, arrowwood, vine maple, laurel, alder, and salmonberry.

N. 89°48' W., along the N. bdy. of sec. 4.

Ascend 71 ft. over SE. slope, changing to S. slope.

8.36

The closing cor. of secs. 33 and 34, T. 22 S., R. 6 W., determined at record distance from the remains of the original bearing trees:

A fir, dead and down, 50 ins. diam., bears N. 83° W., 100 lks. dist., mkd. T22S R6W S33 CC BT. (Record bearing, N. 62° W.)

A stump hole, bears N. 55° E., 21 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C C
T22SR6W
S33 | S34
S 4
T23SR6W
1955

*FD. B.C. 6/92
J. BRANCH
M115-23*

from which

A fir, 7 ins. diam., bears N. 33° E., 25 lks. dist.,
mkd. T22S R6W S34 CC BT.

A fir, 6 ins. diam., bears N. 67° W., 36 lks. dist.,
mkd. T22S R6W S33 CC BT.

Descend 40 ft. over SW. slope.

10.42

Ravine, drains S. 45° E.; asc. 207 ft. over SE. slope, changing to S. slope.