

County Surveyor's Record, Douglas County, Oregon
11

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS

A stump hole, bears N. 33° W., 40 lks. dist.,
with fallen log mkd. T22 on exposed and burned blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground
to solid rock, and in a mound of stone, 6 ft. base, to top, with
brass cap mkd.

*FD. 5K
3-91 M III-72*

C C
T22SR6W
S31 | S32
S 6
1955

Descend 88 ft. along N. slope, changing to NW. slope.

12.70 Creek, 1 lk. wide, course N. 10° E.; asc. 186 ft. over E. slope.

17.74 Spur, slopes N.; desc. 102 ft. along broken N. slope.

29.20 Spur, slopes N. 60° W.; desc. 69 ft. over SW. slope.

31.25 Creek, 1 lk. wide, course N. 45° W.; desc. 112 ft. along broken N.
slope.

36.98 Creek, 1 lk. wide, course N.; asc. 82 ft. over E. slope, changing
to N. slope.

39.68 The standard $\frac{1}{4}$ sec. cor. of sec. 6 only, determined at record bear-
ing and distance from the remains of the original bearing trees:

A fir, 35 ins. diam., bears S. 52° E.,
mkd. SC $\frac{1}{4}$ S6 CS BT.

A fir stump, 55 ins. diam., bears S. 39° W.,
mkd. SC $\frac{1}{4}$ S6 CS BT.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$ S 6
S C
1955

*FD. 10/90
C.S. 63/127*

from which

A fir, 10 ins. diam., bears S. 13° E., 30 lks. dist.,
mkd. $\frac{1}{4}$ S6 SC BT.

A chinquapin, 7 ins. diam., bears S. 34° W., 51 lks. dist.,
mkd. $\frac{1}{4}$ S6 SC BT.

N. 89°41' W., beginning new measurement.

Descend 191 ft. over NW. slope.

14.99 Squaw Creek, 12 lks. wide, course S. 60° W.; asc. 9 ft. over S.
slope.

21.58 Creek, 1 lk. wide, course S. 20° E.; asc. 153 ft. along broken S.
slope.

40.30 The standard cor. of Tps. 23 S., Rs. 6 and 7 W., is determined at
record bearing and distance from the only original bearing tree: