

County Surveyor's Record, Douglas County, Oregon  
12

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS

A fir, 30 ins. diam., bears S. 54° E., 59 lks. dist.,  
with healed blaze.

This standard cor. is changed to an angle point.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground,  
with brass cap mkd.

*FD. 10/90  
C.S. 63/127*

A P  
T22SR6W  
S 31  
1956

from which

A dogwood, 7 ins. diam., bears S. 56° E., 38 lks. dist.,  
mkd. AP T23S R6W S6 BT.

A chinquapin, 12 ins. diam., bears N. 81° W., 119 lks. dist.,  
mkd. AP T22S R6W S31 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, and  
cedar. Undergrowth, vine maple, poison oak, salmonberry, alder,  
and salal.

N. 87°50' W., beginning new measurement.

Descend 59 ft. over S. slope, changing to SW. slope.

5.10

Point for the closing cor. of Tps. 23 S., Rs. 6 and 7 W., at pro-  
portionate distance; there is no remaining evidence of the original  
corner, hereinafter described.

Reestablishment of the surveys executed by Gordon and Gardner,  
Deputy Surveyors, in 1853, and partly resurveyed by W. H. Byars,  
Deputy Surveyor, in 1881, and partly resurveyed by Carl S. Nicklin,  
Deputy Surveyor, in 1897.

Continue N. 87°50' W., with the dependent resurvey of 5th Stan.  
Par. S., N. Bdy. T. 23 S., R. 7 W., along the N. bdy. of sec. 1.

Descend 39 ft. over SW. slope, changing to W. slope.

6.70

Point for the closing cor. of Tps. 22 S., Rs. 6 and 7 W., deter-  
mined longitudinally by the intersection of a blazed line, and  
latitudinally by the standard  $\frac{1}{4}$  sec. cor. of sec. 36, T. 22 S., R.  
7 W., which bears N. 87°50' W., 32.78 chs. dist.

This closing cor. is now restored as the cor. of Tps. 22 S., Rs. 6  
and 7 W.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground,  
with brass cap mkd.

*FO OK  
3-91-M111-72*

T22S  
R7W | R6W  
S36 | S31  
1956

from which

A fir, 8 ins. diam., bears N. 38 $\frac{1}{2}$ ° E., 91 lks. dist.,  
mkd. T22S R6W S31 BT.

A fir, 34 ins. diam., bears N. 40° W., 75 lks. dist.,  
mkd. T22S R7W S36 BT.

Continue N. 87°50' W., with the dependent resurvey of the 5th Stan.  
Par. S., S. Bdy. T. 22 S., R. 7 W. along the S. bdy. of sec. 36.