

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the 5th Stan. Par. S., N. Bdy. T. 23 S., R. 6 W.

CHAINS	<p>Descend 53 ft. over W. slope.</p> <p>8.20 Road, improved, 30 lks. wide, bears S. 10° E. and N. 30° W.; desc. 50 ft. over W. slope.</p> <p>10.70 Fence, 3 strand barb-wire, bears S. 45° E. and N. 45° W., thence over level land.</p> <p>13.40 Brush Creek, 40 lks. wide, course N. 30° W., thence over level land.</p> <p>18.00 Fence, 3 strand barb-wire, bears S. 20° E. and N. 20° W., thence over level land.</p> <p>18.90 Creek, 2 lks. wide, course N. 60° E.; edge of timber, bears NE. and SW.; asc. 124 ft. over SE. slope.</p> <p>23.70 Spur, slopes N. 70° E.; desc. 28 ft. along N. slope.</p> <p>32.50 Creek, 3 lks. wide, course N. 50° E.; asc. 205 ft. over SE. slope.</p> <p>39.48 The standard $\frac{1}{4}$ sec. cor. of sec. 36 only, determined at record bearing and distance from the remains of one of the original bearing trees:</p> <p style="padding-left: 40px;">A fir stump, 14 ins. diam., bears N. 84° W., 32 lks. dist., mkd. S 4.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div style="font-family: cursive;"> <p>FO. OK 2/9+137 HOFFMANN E.S. 63/154-5</p> </div> <div style="text-align: center;"> <p>T22SR7W S C $\frac{1}{4}$ S 36 1956</p> </div> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 41° E., 47 lks. dist., mkd. $\frac{1}{4}$ S36 SC BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 8° W., 54 lks. dist., mkd. $\frac{1}{4}$ S36 SC BT.</p> <p>Land, E. half cultivated, W. half mountainous and timbered. Soil, rocky clay. Timber, fir, and hemlock. Undergrowth, poison oak, salal, vine maple, salmonberry, and alder.</p>
--------	--

Dependent Resurvey of the East Boundary, T. 23 S., R. 6 W.

"Reestablishment of the survey executed by Elder and Gile, Deputy Surveyors, in 1853."

The cor. of Tps. 23 and 24 S., Rs. 5 and 6 W., is determined at the cor. of fences, extending N., S., E., and W., which point has been recognized and accepted by local residents for more than 40 years.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.