

County Surveyor's Record, Douglas County, Oregon  
14

Dependent Resurvey of the East Boundary, T. 23 S., R. 6 W.

CHAINS

T23S  
R6W | R5W  
S36 | S31  
S 1 | S 6  
T24S  
1943

from which

A fir, 60 ins. diam., bears N.  $57\frac{1}{2}^\circ$  E., 60 lks. dist.,  
mkd. T23S R5W S31 BT.

A fir, 35 ins. diam., bears S.  $62\frac{1}{2}^\circ$  E., 127 lks. dist.,  
mkd. T24S R5W S6 BT.

A fir, 36 ins. diam., bears S.  $18\frac{1}{2}^\circ$  W., 177 lks. dist.,  
mkd. T24S R6W S1 BT.

A fir, 38 ins. diam., bears N.  $83\frac{1}{2}^\circ$  W., 280 lks. dist.,  
mkd. T23S R6W S36 BT.

N.  $0^\circ 01'$  W., bet. secs. 31 and 36, marking and blazing the true line.

Ascend 106 ft. over SW. slope, through heavy timber and dense undergrowth.

7.35 Spur, slopes N.  $60^\circ$  W.; desc. 502 ft. over NE. slope.

32.15 Creek, 8 lks. wide, course E.; asc. 195 ft. over SW. slope.

39.63 The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, determined at record bearing and distance from the original bearing trees:

An oak, 20 ins. diam., bears S.  $37\frac{1}{2}^\circ$  E., 19 lks. dist.,  
marks grown over.

An oak, 26 ins. diam., bears N.  $2^\circ$  W., 13 lks. dist.,  
marks grown over.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,  
with brass cap mkd.

*Fd. OK  
Ken Hoffine  
M117-52  
July 1993*

$\frac{1}{4}$   
S 36 | S 31  
1943

N.  $0^\circ 07'$  E., beginning new measurement.

Ascend 85 ft. over SW. slope.

6.80 Spur, slopes W.; desc. 128 ft. over NW. slope, changing to NE. slope.

37.00 Dry bed of creek, 5 lks. wide, course E.; over rolling land.

38.30 Road, unimproved, bears E. and W.

40.29 The cor. of secs. 25, 30, 31, and 36, determined at record bearing and distance from the original bearing trees:

An oak, 22 ins. diam., bears N.  $34^\circ$  E., 185 lks. dist.,  
marks grown over.