

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the East Boundary, T. 23 S., R. 6 W.

CHAINS

- A fir, 36 ins. diam., bears S. 21° E., 48 lks. dist., mkd. T23S R5W S7 BT.
- A fir, 24 ins. diam., bears S. 15½° W., 304 lks. dist., mkd. T23S R6W S12 BT.
- A cedar, 16 ins. diam., bears N. 55° W., 72 lks. dist., mkd. T23S R6W S1 BT.

Land, mountainous. Soil, sandy and rocky loam. Timber, fir, cedar, and hemlock. Undergrowth, salal, vine maple, alder, yew, huckleberry, fern, manzanita, chinquapin, and poison oak.

N. 0°13' E., bet. secs. 1 and 6.

Ascend 101 ft. over SW. slope, through heavy timber and dense undergrowth.


- 3.50 Spur, slopes S. 10° E.; asc. 222 ft. over SE. slope.
- 15.75 Spur, slopes S. 45° W.; desc. 157 ft. over NW. slope.
- 28.70 Spur, slopes N. 45° W.; desc. 352 ft. over NE. slope, changing to N. slope.
- 39.76 The ¼ sec. cor. of secs. 1 and 6, perpetuated with a stake, 30 ins. long, 4 ins. sq., firmly set, mkd. ¼ on W. side, from which the original bearing trees:

A fir stump, 36 ins. diam., bears S. 48° E., 57 lks. dist., marks burned off.

A fir stump, 30 ins. diam., bears S. 35° W., 48 lks. dist., mkd. BT.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.



from which

A fir, 6 ins. diam., bears N. 84° E., 30 lks. dist., mkd. ¼ S6 BT.

A fir, 26 ins. diam., bears S. 76½° W., 70 lks. dist., mkd. ¼ S1 BT.

N. 0°06' E., beginning new measurement.

Descend 272 ft. over N. slope, changing to NW. slope.

- 9.70 Road, gravelled, 40 lks. wide, bears N. 45° E. and S. 45° W.
- 10.40 Leave heavy timber and dense undergrowth, bears NE. and SW.; enter field, bears E. and W.
- 25.50 Leave field, bears E. and W.; enter heavy timber and dense undergrowth, bears E. and W.