

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the East Boundary, T. 23 S., R. 6 W.

CHAINS
25.95

Creek, 10 lks. wide, course E.; asc. 43 ft. over SE. slope.

26.00

Top of slope, bears E. and W.; along gradual E. slope.

39.54

The standard cor. of Tps. 23 S., Rs. 5 and 6 W.

Land, mountainous. Soil, sandy and rocky loam. Timber, fir, cedar, and hemlock. Undergrowth, poison oak, salal, madrone, chinquapin, manzanita, laurel, Oregon grape, and poison oak.

Dependent Resurvey of the South Boundary, T. 23 S., R. 6 W.

"Reestablishment of the surveys executed by Robert Elder and Henry Gile, Deputy Surveyors, in 1853, and a resurvey of the S. bdrs. of sections 32 and 33, executed by William R. Whipple, Deputy Surveyor, in 1891."

From the cor. of Tps. 23 and 24 S., Rs. 5 and 6 W.

N. 89°43' W., bet. secs. 1 and 36, marking and blazing the true line.

Descend 87 ft. over SW. slope, through heavy timber and dense undergrowth.

8.95

Ravine, course S.; asc. 135 ft. over SE. slope.

24.20

Spur, slopes N.; desc. 94 ft. over NW. slope.

40.11

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 36 \\ S 1 \\ 1943 \end{array}$$

from which

A fir, 12 ins. diam., bears N. 76° W., 49 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

A fir, 48 ins. diam., bears S. 10° E., 147 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Descend 61 ft. over broken NW. slope, changing to SW. slope.

50.00

Head of draw, drains S.; asc. 120 ft. over SE. slope.

51.50

Road, bears N. and S.

70.10

Spur, slopes S. 20° E.; desc. 34 ft. over SW. slope.

64.80

Head of draw, drains S.; asc. 120 ft. over SE. slope.

80.22

The cor. of secs. 1, 2, 35, and 36, the rotted remains of old stake, 30 ins. long, 4 ins. sq., marked S 36 on NE., T. 24 S1 on SE. S2 on SW., and R6W S35 on NW. face, tied to cor. of fences, extending E., W., and S.

At the corner point