

County Surveyor's Record, Douglas County, Oregon
23

Dependent Resurvey of the South Boundary, T. 23 S., R. 6 W.

CHAINS

A dead and fallen fir, 24 ins. diam., bears S. 27° E.,
21 lks. dist., marks rotted off.

A dead and fallen fir, 24 ins. diam., bears S. 25° W.,
18 lks. dist., marked BT.

A dead and fallen fir, 15 ins. diam., bears N. 33° W.,
23 lks. dist., marks rotted off.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
with brass cap mkd.

T23SR6W
S34 | S35
S 3 | S 2
T24S
1943

from which

A cedar, 16 ins. diam., bears N. 57½° E., 33 lks. dist.,
mkd. T23S R6W S35 BT.

A fir, 40 ins. diam., bears S. 30½° E., 66 lks. dist.,
mkd. T24S R6W S2 BT.

A fir, 60 ins. diam., bears S. 45° W., 69 lks. dist.,
mkd. T24S R6W S3 BT.

A cedar, 40 ins. diam., bears N. 57½° W., 42 lks. dist.,
mkd. T23S R6W S34 BT.

Land, mountainous. Soil, sandy and rocky loam. Timber, fir,
cedar, and hemlock. Undergrowth, poison oak, alder, salal, laurel,
madrone, huckleberry, manzanita, and Oregon grape.

N. 89°35' W., bet. secs. 3 and 34.

Descend 4 ft. over SW. slope.

0.22 Creek, 2 lks. wide, course N. 45° W.; asc. 3 ft. over NE. slope.

1.22 Top of ridge, bears N. 45° W. and S. 45° E.; desc. 270 ft. over
NW. slope.

39.98 Point for witness to the ¼ sec. cor. of secs. 3 and 34.

Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

W C
T23SR6W
¼ S 34
S 3
T24S
1957

from which

A fir, 8 ins. diam., bears N. 1½° E., 28 lks. dist.,
mkd. XBT.

A fir, 8 ins. diam., bears S. 10¼° E., 17 lks. dist.,
mkd. XBT.