

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary, T. 23 S., R. 6 W.

CHAINS
40.09

The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, determined at record distance and bearing from the original bearing trees:

A fir, 40 ins. diam., bears S. 84° W., 71 lks. dist., with healed blaze.

A fir, 33 ins. diam., bears N. 57° W., 25 lks. dist., mkd. BT.

The point for cor. falls on the roots of a fir, dead and down, where it is impracticable to establish a permanent monument.

N. 89°35' W., beginning new measurement.

Ascend 42 ft. over NE. slope.

6.43 Ridge, bears S. 35° E. and N. 35° W.; desc. 344 ft. over SW. slope.

36.15 Bottom of steep descent, bears N. and S.; desc. 3 ft. over slight SW. slope.

38.94 Yellow Creek, 20 lks. wide, 1 lk. deep, courses S. 5° W., curving to S. 40° W.; asc. 114 ft. over E. slope.

40.32 The cor. of secs. 3, 4, 33, and 34, determined at record bearing and distance from one of the original bearing trees:

A fir, 48 ins. diam., bears S. 71° W., 17 lks. dist., marks rotted off.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23SR6W
S33 S34
S 4 S 3
T24S
1957

Fd. O. K. by
H. J. JOHNSON
5-6-82
M 9 2 - 17
from which

A fir, 9 ins. diam., bears N. 51 $\frac{1}{2}$ ° E., 49 $\frac{1}{2}$ lks. dist., mkd. T24S R6W S34 BT.

A fir, 22 ins. diam., bears S. 32 $\frac{1}{2}$ ° E., 47 lks. dist., mkd. T24S R6W S3 BT.

A fir, 21 ins. diam., bears S. 49° W., 58 lks. dist., mkd. T24S R6W S4 BT.

No bearing tree available in sec. 33.

Land, rolling hills, moderate slopes. Soil, sandy loam, rock outcrops. Timber, fir, hemlock, cedar, and maple. Undergrowth, vine maple, alder, madrone, salal, and salmonberry.

N. 89°40' W., bet. secs. 4 and 33.

Ascend 3 ft. over E. slope.

1.69 Dry bed of a creek, 8 lks. wide, drains S.; asc. 349 ft. over E. slope, changing to SE. slope.