

County Surveyor's Record, Douglas County, Oregon
25

Dependent Resurvey of the South Boundary, T. 23 S., R. 6 W.

CHAINS
13.84

Ridge, bears N. and S.; desc. 36 ft. over SW. slope.

16.78

Swale, drains S.; asc. 159 ft. over E. slope, changing to SE. slope.

27.24

Ridge, bears N. and S.; desc. 128 ft. over SW. slope.

40.39

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, determined at record bearing and distance from the remains of an original bearing tree:

A fir, 37 ins. diam., bears N. $50\frac{3}{4}^\circ$ W., 50 lks. dist.,
mkd. BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T23SR6W
 $\frac{1}{4}$ S 33
S 4
T24S
1957

*Fd. OK. by
H. JOHNSTONE
5-6-82
M 92-17*

from which

A fir, 6 ins. diam., bears N. $25\frac{1}{4}^\circ$ E., 61 lks. dist.,
mkd. $\frac{1}{4}$ S33 BT.

A fir, 16 ins. diam., bears S. $76\frac{1}{2}^\circ$ E., 91 lks. dist.,
mkd. $\frac{1}{4}$ S4 BT.

S. $89^\circ 45'$ W., beginning new measurement.

Descend 100 ft. over SW. slope, through heavy timber and scattering
undergrowth.

5.29

Ravine, drains S. 20° E.; edge of logged area, bears N. and S.;
asc. 316 ft. over SE. slope.

16.94

Ridge, bears NW. and SE.; desc. 167 ft. over SW. slope, changing
to SE. slope.

23.72

Leave logged area, edge of timber, bears N. and S.; desc. 85 ft.
over SW. slope.

27.18

Dry ravine, drains S.; asc. 129 ft. over E. slope.

33.72

Spur, slopes S. 35° E.; asc. 129 ft. over SE. slope.

40.86

Point for the cor. of secs. 4, 5, 32, and 33, at proportionate
distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 5 ins. in the ground,
to solid rock, and in a mound of stone, 4 ft. base, to top, with
brass cap mkd.

T23SR6W
S32 | S33
S 5 | S 4
T24S
1957

from which

A fir, 16 ins. diam., bears N. 38° E., 47 lks. dist.,
mkd. T23S R6W S33 BT.

A fir, 11 ins. diam., bears S. $17\frac{1}{2}^\circ$ E., 60 lks. dist.,
mkd. T24S R6W S4 BT.