

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary, T. 23 S., R. 6 W.

CHAINS

A fir, 18 ins. diam., bears S. 85° W., 50 lks. dist.,
mkd. T24S R6W S5 BT.

A fir, 16 ins. diam., bears N. 27½° W., 31 lks. dist.,
mkd. T23S R6W S32 BT.

Land, rolling hills, moderately steep slopes. Soil, sandy loam,
outcropping of rock. Timber, fir, hemlock, and cedar. Undergrowth,
vine maple, madrone, alder, salal, blackberry and poison oak.

S. 89°45' W., bet. secs. 5 and 32.

Ascend 17 ft. over SE. slope.

- 1.91 Ridge, bears N. and S.; desc. 286 ft. over W. slope, changing
to SW. slope.
- 18.10 Top of bluff, 60 ft. high, faces SW.
- 18.88 Base of bluff; desc. 315 ft. over SW. slope.
- 29.76 Enter logged area, edge bears N. and S.; desc. 98 ft. over SW.
slope.
- 39.31 Logging road, 20 lks. wide, bears N. 35° E. and S. 35° W.; desc.
50 ft. over SW. slope.
- 40.86 The ¼ sec. cor. of secs. 5 and 32, determined at record bearing
and distance from the remains of the original bearing trees:
- A fir stump, 56 ins. diam., bears N. 48° E., 59 lks. dist.,
mkd. ¼ S32 BT.
- A fir, 30 ins. diam., bears S. 72° E., 59 lks. dist.,
mkd. ¼ S5.
- At the corner point
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
- T23SR6W
¼ S 32
S 5
T24S
1957
- from which
- A hemlock, 10 ins. diam., bears N. 58° W., 11½ lks. dist.,
mkd. ¼ S32 BT.
- A fir, 16 ins. diam., bears S. 61° W., 79½ lks. dist.,
mkd. ¼ S5 BT.
-
- N. 89°56' W., beginning new measurement.
- Descend 64 ft. over SW. slope, through logged area.
- 5.82 Road, unimproved, 20 lks. wide, bears S. 35° E. and N. 35° W.;
desc. 95 ft. over W. slope.
- 9.19 Road, gravelled, 40 lks. wide, bears S. 10° E. and N. 10° W.;
desc. 52 ft. over W. slope.
- 12.87 Bear Creek, 15 lks. wide, 1 lk. deep, course S. 5° E.; asc. 249 ft.
over steep E. slope.