

# County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey of the South Boundary, T. 23 S., R. 6 W.

CHAINS

Descend 215 ft. over S. slope.

50.84

Spur, slopes SW.; desc. 91 ft. over W. slope.

61.45

Creek, 8 lks. wide, course S. 25° E.; asc. 530 ft. over E. slope, changing to NE. slope.

77.50

Point for the cor. of Tps. 23 and 24 S., Rs. 6 and 7 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S	
R7W	R6W
S36	S31
S 1	S 6
T24S	
1957	

from which

A fir, 22 ins. diam., bears N. 75½° E., 117 lks. dist., mkd. T23S R6W S31 BT.

A fir, 20 ins. diam., bears S. 63° E., 193 lks. dist., mkd. T24S R6W S6 BT.

A fir, 12 ins. diam., bears S. 82°45' W., 143 lks. dist., mkd. T24S R7W S1 BT.

A fir, 18 ins. diam., bears N. 66°45' W., 184 lks. dist., mkd. T23S R7W S36 BT.

From this point the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of T. 24 S., R. 7 W., bears S. 2°08' W., 79.05 chs. dist., described in the field notes of the Dependent Resurvey of a Portion of the E. Bdy. of T. 24 S., R. 7 W., of this Group.

From this same point the cor. of secs. 35 and 36 only, S. bdy. T. 23 S., R. 7 W., bears N. 89°16' W., 77.49 chs. dist., described in the field notes of the Dependent Resurvey of a Portion of the S. Bdy. T. 23 S., R. 7 W., of this Group.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, poison oak, vine maple, hazel, blackberry, and alder.

## Dependent Resurvey of the West Boundary, T. 23 S., R. 6 W.

(Reestablishment of the survey executed by W. H. Byars,  
Deputy Surveyor, in 1881)

From the cor. of Tps. 23 and 24 S., Rs. 6 and 7 W.

N. 0°14' W., bet. secs. 31 and 36.

Ascend 6 ft. over S. slope.

0.35

Road, unimproved, 15 lks. wide, bears E. and W.; asc. 4 ft. over S. slope.

0.98

Ridge, bears E. and W.; desc. 321 ft. over N. slope.