

# County Surveyor's Record, Douglas County, Oregon

29

## Dependent Resurvey of the West Boundary, T. 23 S., R. 6 W.

CHAINS  
11.08

Creek, 8 lks. wide, course E.; asc. 434 ft. over S. slope.

28.00

Road, unimproved, 20 lks. wide, bears N. 70° E. and S. 70° W.; asc. 17 ft. over SW. slope.

28.70

Spur, slopes N. 40° W.; desc. 281 ft. over N. slope.

39.495

Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23S	
$\frac{1}{4}$	
R7W	R6W
S36	S31
1957	

from which

A hemlock, 17 ins. diam., bears N. 51° E., 24 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.A fir, 17 ins. diam., bears N. 29 $\frac{1}{2}$ ° W., 13 lks. dist., mkd.  $\frac{1}{4}$  S36 BT.

Descend 33 ft. over N. slope.

41.72

Edge of logged area, bears E. and W.; desc. 140 ft. over N. slope.

45.22

Bottom of steep descent, leave logged area, edge bears E. and W.; road, unimproved, 15 lks. wide, bears E. and W.; desc. 13 ft. over NW. slope.

48.30

Bed of dry creek, 3 lks. wide, course S. 70° W.; asc. 10 ft. over SW. slope.

54.10

Spur, slopes NW.; desc. 133 ft. over NW. slope.

59.52

Spur, slopes W.; desc. 387 ft. over N. slope, changing to NW. slope.

69.25

Creek, 5 lks. wide, course N. 45° E.; asc. 12 ft. along SE. slope.

71.65

Spur, slopes E.; desc. 77 ft. over NE. slope.

75.58

Creek, 5 lks. wide, course N. 15° W.; asc. 16 ft. over W. slope.

78.99

Point for the cor. of secs. 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23S	
R7W	R6W
S25	S30
S36	S31
1957	

from which

A fir, 13 ins. diam., bears N. 85° E., 20 lks. dist., mkd. T23S R6W S30 BT.

A fir, 8 ins. diam., bears S. 2° E., 42 lks. dist., mkd. T23S R6W S31 BT.