

# County Surveyor's Record, Douglas County, Oregon

31

Dependent Resurvey of the West Boundary, T. 23 S., R. 6 W.

CHAINS  
78.99

The cor. of secs. 19, 24, 25, and 30, determined at record bearing and distance from the only remaining bearing tree:

A fir, 32 ins. diam., bears N. 30° W., 119 lks. dist.,  
mkd. BT on face of opened blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T23S	
R7W	R6W
S24	S19
S25	S30
1957	

from which

A fir, 14 ins. diam., bears N. 14° E., 43 lks. dist.,  
mkd. T23S R6W S19 BT.

A fir, 20 ins. diam., bears S. 64°30' E., 50 lks. dist.,  
mkd. T23S R6W S30 BT.

A fir, 29 ins. diam., bears S. 9°30' W., 79 lks. dist.,  
mkd. T23S R7W S25 BT.

Land, mountainous, steep slopes. Soil, sandy loam, sandstone outcrops. Timber, fir, hemlock, and cedar. Undergrowth, salal, vine maple, alder, blackberry, and madrone.

N. 0°32' W., bet. secs. 19 and 24.

Descend 73 ft. over NW. slope.

3.55 Creek, 2 lks. wide, course N. 60° W.; asc. 20 ft. over SW. slope.

8.00 Ridge, bears E. and W.; desc. 114 ft. over N. slope.

14.18 Creek, 4 lks. wide, course N. 65° W.; asc. 4 ft. over SW. slope.

17.10 Ridge, bears E. and W.; desc. 17 ft. over W. slope.

18.45 Swale, drains N. 70° W.; asc. 10 ft. over SW. slope.

25.70 Ridge, bears E. and W.; desc. 40 ft. over NW. slope.

29.60 Creek, 5 lks. wide, course S. 35° W.; asc. 245 ft. over SE. slope, changing to S. slope.

39.20 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, determined at record bearing and distance from an original bearing tree:

A cedar, 36 ins. diam., bears N. 25° E., 52 lks. dist.,  
mkd. BT on exposed face.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T23S	
$\frac{1}{4}$	
R7W	R6W
S24	S19
1957	

*Fd QK.*  
*by*  
*D. BAKER*  
*Nov 1982*  
*M 93-23*