

Dependent Resurvey of the West Boundary, T. 23 S., R. 6 W.

CHAINS  
39.63

The  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, determined from the original bearing trees:

A cedar, 30 ins. diam., bears N. 40° E., 5 lks. dist., with healed blaze.

A cedar, 22 ins. diam., bears S. 85° W., 14 lks. dist., with marks BT on exposed face.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T23S  
 $\frac{1}{4}$   
R7W | R6W  
S13 | S18  
1957

from which

A fir, 12 ins. diam., bears S. 39° E., 51 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

A fir, 20 ins. diam., bears S. 39 $\frac{1}{2}$ ° W., 43 lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

N. 0°38' E., beginning new measurement.

Ascend 2 ft. over W. slope.

3.90 Ridge, bears N. 40° W. and S. 40° E.; desc. 44 ft. over NE. slope.

7.84 Edge of ridge, bears N. 15° W. and S. 15° E.; desc. 400 ft. over steep NE. slope.

19.83 Creek, 10 lks. wide, course N. 40° W.; asc. 203 ft. over SW. slope.

34.34 Spur, slopes W.; desc. 9 ft. over NW. slope.

38.08 Creek, 1 lk. wide, course N. 70° W.; asc. 5 ft. over SW. slope.

39.45 The cor. of secs. 7, 12, 13, and 18, determined at record bearing and distance from the original bearing trees:

A fir, dead and down, bears N. 12° E., 31 lks. dist., marks rotted off.

A fir, 34 ins. diam., bears S. 68° E., 39 lks. dist., mkd. 6W S18 on exposed face of chopped blaze.

A fir, dead and down, bears S. 8° W., 49 lks. dist., with healed blaze.

A fir, dead and down, bears N. 12° W., 28 lks. dist., with rotted face.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T23S  
R7W | R6W  
S12 | S 7  
S13 | S18  
1955