

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the West Boundary, T. 23 S., R. 6 W.

CHAINS

from which

A hemlock, 8 ins. diam., bears N. 81° E., 49 lks. dist.,
mkd. T23S R6W S7 BT.

A fir, 9 ins. diam., bears S. 43° E., 56 lks. dist.,
mkd. T23S R6W S18 BT.

A white fir, 14 ins. diam., bears S. 30° W., 51 lks. dist.,
mkd. T23S R7W S13 BT.

A white fir, 10 ins. diam., bears N. 39° W., 60 lks. dist.,
mkd. T23S R7W S12 BT.

This corner is established on spur, slopes W.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, vine maple, poison oak, alder, maple, and madrone.

N. 0°40' W., bet. secs. 7 and 12.

Descend 68 ft. over NW. slope.

4.30 Creek, 2 lks. wide, course N. 65° W.; asc. 26 ft. over SW. slope.

4.99 Spur, slopes W.; desc. 3 ft. over NW. slope.

5.80 Creek, 2 lks. wide, course S. 50° W.; asc. 277 ft. over SW. slope, changing to S. slope.

17.58 Trail, bears N. 80° W. and S. 80° E.; ridge, bears E. and W.; desc. 68 ft. over N. slope, changing to NW. slope.

30.42 Head of ravine, drains W.; asc. 102 ft. over SW. slope.

38.67 Spur, slopes N. 20° W.; desc. 93 ft. over NE. slope, changing to N. slope.

39.335 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T23S
 $\frac{1}{4}$
R7W | R6W
S12 | S 7
1957

from which

A fir, 7 ins. diam., bears S. 21° E., 72 lks. dist.,
mkd. $\frac{1}{4}$ S7 BT.

A hemlock, 7 ins. diam., bears N. 49° W., 12 lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

Descend 418 ft. over N. slope.

50.80 Creek, 8 lks. wide, course W.; asc. 158 ft. over S. slope.

54.04 Road, improved, 30 lks. wide, bears E. and W.; asc. 265 ft. over S. slope, changing to SW. slope.