

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

(Reestablishment of the survey executed by W. Thiel, Deputy Surveyor in 1873, and J. McQuinn, Deputy Surveyor, in 1883)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.

N. $2^{\circ}58'$ W., bet. secs. 35 and 36, marking and blazing the true line.

Ascend 171 ft. over SE. slope, through heavy timber and dense undergrowth.


4.15 Spur, slopes S. 80° E.; desc. 250 ft. over NE. slope.14.00 Creek, 3 lks. wide, course N. 75° E.; asc. 231 ft. over SE. slope.

20.70 Spur, slopes E.; desc. 271 ft. over NE. slope.

30.00 Creek, 3 lks. wide, course E.; asc. 74 ft. over SE. slope.

39.72 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.



from which

A fir, 30 ins. diam., bears N. 27° E., 50 lks. dist., mkd. $\frac{1}{4}$ S36 BT.A fir, 28 ins. diam., bears S. 69° W., 31 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

Ascend 79 ft. over SE. slope.

43.70 Spur, slopes N. 75° E.; desc. 64 ft. over NE. slope.

54.15 Ravine, drains E.; asc. 172 ft. over SE. slope.

67.00 Spur, slopes E.; desc. 31 ft. over NE. slope.

71.00 Creek, 1 lk. wide, course S. 70° E.; asc. 325 ft. over SE. slope.76.00 Ridge, bears N. 30° E. and S. 30° W.; trail bears N. 30° E. and S. 30° W.; desc. 50 ft. over NW. slope.

79.44 The cor. of secs. 25, 26, 35, and 36, determined by reference to the record bearing and distance to two of the original bearing trees:

A rotted fir stump, 10 ins. diam., bears S. $47\frac{3}{4}^{\circ}$ E., 52 lks. dist., mks. rotted off.A cedar, 36 ins. diam., bears N. $45\frac{3}{4}^{\circ}$ W., 64 lks. dist., mkd. T23 with other marks grown over.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.