

County Surveyor's Record, Douglas County, Oregon
38

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

T23SR6W
S26 | S25
S35 | S36
 1943

from which

A white fir, 9 ins. diam., bears N. 86° E., 176 lks. dist.,
 mkd. T23S R6W S25 BT.

A white fir, 16 ins. diam., bears S. 16° E., 85 lks. dist.,
 mkd. T23S R6W S36 BT.

A fir, 12 ins. diam., bears S. 66½° W., 27 lks. dist.,
 mkd. T23S R6W S35 BT.

A white fir, 6 ins. diam., bears N. 79° W., 74 lks. dist.,
 mkd. T23S R6W S26 BT.

Land, mountainous. Soil, sandy and rocky loam. Timber, fir,
 cedar, and hemlock. Undergrowth, alder, salal, madrone, poison
 oak, chinquapin, laurel, bracken fern, manzanita, and syringa.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the
 Tp.

S. 89°43' W., bet. secs. 25 and 36.

Ascend 49 ft. over SE. slope.

7.18 Road, bears N. and S.

9.00 Spur, slopes S.; desc. 80 ft. over SW. slope.

17.55 Leave timber, edge bears NW. and SE.; enter field, edge bears NW.
 and SE.

20.85 Creek, 2 lks. wide, course S. 10° W.; over gradual S. slope.

28.70 Creek, 2 lks. wide, course S. 45° E.; asc. 84 ft. over E. slope.

35.58 Leave field, edge bears N. and S.; enter heavy timber and dense
 undergrowth, edge bears N. and S.

45.43 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, determined at record bearing
 and distance from the original bearing trees:

A black oak, 30 ins. diam., bears S. 82° E., 116 lks. dist.,
 with chopped blaze.

A madrone, 34 ins. diam., bears N. 46½° W., 28 lks. dist.,
 mkd. $\frac{1}{4}$ S. on opened blaze.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
 with brass cap mkd.

$\frac{1}{4}$ S 25
S 36
 1957

from which

A chinquapin, 7 ins. diam., bears N. 15½° W., 50 lks. dist.,
 mkd. $\frac{1}{4}$ S25 BT.

A fir, 9 ins. diam., bears S. 23° W., 19 lks. dist.,
 mkd. $\frac{1}{4}$ S36 BT.