

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

S. 89°41' W., beginning new measurement.

Ascend 331 ft. over broken E. slope.

25.35 Ravine, drains S. 45° E.; asc. 328 ft. over E. slope, changing to SE. slope.

36.00 Ridge, bears N. 30° E. and S. 30° W.; desc. 31 ft. over NW. slope.

36.15 Trail, bears N. 30° E. and S. 30° W.

38.97 The cor. of secs. 25, 26, 35, and 36.

Land, mountainous. Soil, sandy and rocky loam. Timber, fir, cedar, and hemlock. Undergrowth, poison oak, vine maple, madrone, laurel, syringa, alder, manzanita, and huckleberry.

N. 11°05' E., bet. secs. 25 and 26.


Descend 244 ft. over broken NW. slope, through heavy timber and dense undergrowth.

39.62 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, determined by reference to the record bearing and distance to one of the original bearing trees:

A fir, 30 ins. diam., bears E., 77 lks. dist.,  
mkd.  $\frac{1}{4}$ .

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.



from which


A fir, 14 ins. diam., bears N.  $76\frac{3}{4}^\circ$  W., 60 lks. dist.,  
mkd.  $\frac{1}{4}$  S26 BT.

N. 0°51' W., beginning new measurement.

Descend 168 ft. over NW. slope, through logged area.

19.37 Point for the N  $\frac{1}{16}$  sec. cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A fir, 8 ins. diam., bears S.  $67\frac{1}{2}^\circ$  E., 19 lks. dist.,  
mkd. N  $\frac{1}{16}$  S25 BT.

A fir, 10 ins. diam., bears S.  $50\frac{1}{2}^\circ$  W., 30 lks. dist.,  
mkd. N  $\frac{1}{16}$  S26 BT.

Descend 11 ft. over NW. slope.