

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS
21.85

Road, improved, 40 lks. wide, bears N. 30° E. curving N. and S. 30° W. curving S.; desc. 43 ft. over NW. slope.

35.44

Creek, 1 lk. wide, course N. 80° W.; asc. 9 ft. over SW. slope.

38.74

The cor. of secs. 23, 24, 25, and 26, determined at record bearing and distance from the only remaining bearing tree:

A fir, 36 ins. diam., bears S. 90° E., 80 lks. dist.,
mkd. R6 S2 BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T23SR6W	
S23	S24
S26	S25
1957	

from which

A fir, 9 ins. diam., bears N. 12° E., 33 lks. dist.,
mkd. T23S R6W S24 BT.

A fir, 30 ins. diam., bears S. 66° E., 5 lks. dist.,
mkd. T23S R6W S25 BT.

A chinquapin, 10 ins. diam., bears S. 12° W., 64 lks. dist.,
mkd. T23S R6W S26 BT.

A fir, 10 ins. diam., bears N. 15° W., 40 lks. dist.,
mkd. T23S R6W S23 BT.

Land, moderate slopes. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, poison oak, and vine maple.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.

S. 88°05' W., bet. secs. 24 and 25.

Ascend 380 ft. over NE. slope.

7.97

Spur, slopes S. 30° E.; desc. 60 ft. along S. slope.

16.07

Head of ravine, drains S.; asc. 50 ft. along S. slope.

18.25

Ridge, bears N. 15° E. and S. 15° W.; desc. 5 ft. over W. slope.

19.37

Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	
S 24	S 25
1957	

from which

A maple, 10 ins. diam., bears N. 12½° E., 186 lks. dist.,
mkd. E 1/16 S24 BT.

A fir, 7 ins. diam., bears S. 71° E., 21 lks. dist.,
mkd. E 1/16 S25 BT.

Descend 74 ft. along N. slope.