

# County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS 65.85	S. edge of road, 20 lks. wide, bears N. 80° W. and S. 80° E.; ridge, bears E. and W.; desc. 63 ft. over N. slope.				
70.45	N. edge of road, 20 lks. wide, bears N. 71° W. curving N.; desc. 112 ft. over N. slope.				
77.58	<p>The cor. of secs. 13, 14, 23, and 24, determined at record bearing and distance from the original remaining bearing trees:</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears N. 60½° E., 113 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S. 45½° W., 49 lks. dist., marks grown over.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 22½° W., 40 lks. dist., marks grown over.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23SR6W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S23</td> <td style="padding: 0 5px;">S24</td> </tr> </table> <p>1943</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears N. 48° E., 108 lks. dist., mkd. T23S R6W S13 BT.</p> <p style="padding-left: 40px;">A fir, 60 ins. diam., bears S. 80° E., 75 lks. dist., mkd. T23S R6W S24 BT.</p> <p>Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, poison oak, vine maple, salal, alder, maple, madrone, and syringa.</p>	S14	S13	S23	S24
S14	S13				
S23	S24				
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.</p> <p>S. 86°43' W., bet. secs. 13 and 24.</p> <p>Descend 26 ft. over NW. slope, through heavy timber and dense undergrowth.</p>				
2.40	Head of ravine, drains N.; asc. 40 ft. over NE. slope.				
5.30	Spur, slopes N.; desc. 357 ft. over NW. slope.				
16.30	Ravine, drains N. 10° W.; along N. slope.				
18.75	Creek, 1 lk. wide, course N. 40° E.; asc. 89 ft. over NE. slope.				
20.25	Spur, slopes N. 20° E.; desc. 189 ft. over W. slope.				
24.35	Ravine, course N. 25° W.; asc. 21 ft. over NE. slope.				
27.75	Spur, slopes N.; desc. 79 ft. over NW. slope.				
33.00	Creek, 3 lks. wide, course N. 20° E.; asc. 380 ft. over E. slope.				
40.95	<p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.</p>				