

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

A cedar, 38 ins. diam., bears N. 50° E., 62 lks. dist.,
mkd. T23S R6.

A snag, 36 ins. diam., bears N. 10° W., 60 lks. dist.,
with mks. burned off.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
with brass cap mkd.

T23SR6W
S 2 | S 1
S11 | S12
1943

from which

A fir, 24 ins. diam., bears N. 23 $\frac{1}{4}$ ° E., 46 lks. dist.,
mkd. T23S R6W S1 BT.

A fir, 18 ins. diam., bears S. 35° E., 273 lks. dist.,
mkd. T23S R6W S12 BT.

A fir, 8 ins. diam., bears S. 62° W., 37 lks. dist.,
mkd. T23S R6W S11 BT.

A fir, 30 ins. diam., bears N. 33° W., 98 lks. dist.,
mkd. T23S R6W S2 BT.

Land, mountainous. Soil, sandy and rocky loam. Timber, fir,
cedar, and hemlock. Undergrowth, salal, vine maple, poison oak,
chinquapin, alder, willow, and madrone.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.
S. 82°06' W., bet. secs. 1 and 12.

Descend 140 ft. over SW. slope, through heavy timber and dense
undergrowth.

3.50 Ravine, drains S.; asc. 235 ft. over SE. slope.

9.80 Spur, slopes S.; desc. 433 ft. over SW. slope.

36.25 Junction of roads, 25 lks. wide, gravelled, from N. 20° W.,
S. 40° E., and S. 20° W.

40.55 Creek, 5 lks. wide, course N. 20° W., over rolling land.

41.37 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate
distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground,
with brass cap mkd.

T23SR6W
 $\frac{1}{4}$ S 1
S12
1957

from which

A fir, 20 ins. diam., bears N. 51° W., 473 lks. dist.,
mkd. $\frac{1}{4}$ S1 BT.

A fir, 36 ins. diam., bears S. 49 $\frac{3}{4}$ ° E., 375 lks. dist.,
mkd. $\frac{1}{4}$ S12 BT.

Ascend 492 ft. over SE. slope.