

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS	
10.80	Ridge, bears NE. and SW.; desc. 115 ft. over NW. slope.
12.48	Creek, 2 lks. wide, course N. 35° W.; desc. 37 ft. over NW. slope.
22.07	Creek, 1 lk. wide, course N. 30° W.; asc. 39 ft. over SW. slope.
25.06	Spur, slopes SW.; desc. 56 ft. over W. slope.
40.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <p>T23SR6W</p> <p>↑</p> <p>S34 S35</p> <p>↓</p> <p>1957</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 13° E., 47 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 72$\frac{1}{2}$° W., 121 lks. dist., mkd. $\frac{1}{4}$ S34 BT.</p> <p>Descend 13 ft. over N. slope.</p>
45.70	Swale, drains W.; asc. 46 ft. over SW. slope.
49.90	Spur, slopes N. 45° W.; desc. 300 ft. over NW. slope.
62.00	Creek, 2 lks. wide, course W.; asc. 28 ft. over SW. slope.
63.46	Spur, slopes NW.; desc. 160 ft. over NE. slope.
73.60	Creek, 3 lks. wide, course N. 30° W.; desc. 82 ft. over NW. slope.
78.97	Road, improved, 50 lks. wide, bears N. 75° E. and S. 75° W.
79.09	N. edge of road, improved; desc. 43 ft. over NW. slope.
80.44	The cor. of secs. 26, 27, 34, and 35, determined at record bearing and distance from the remains of an original bearing tree: <div style="margin-left: 40px;"> <p>A maple stub, 36 ins. diam., bears S. 80° E., 16 lks. dist., mkd. T23 S35 BT.</p> </div> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> <p>T23SR6W</p> <p>S27 S26</p> <p>S34 S35</p> <p>1957</p> </div> <p>from which</p> <div style="margin-left: 40px;"> <p>A maple, 25 ins. diam., bears N. 87° E., 215 lks. dist., mkd. T23S R6W S26 BT.</p> <p>A cedar, 30 ins. diam., bears S. 50° E., 49 lks. dist., mkd. T23S R6W S35 BT.</p> </div> </p>

*FD OK 1/6/75
SURVEYOR'S OFFICE
C.S. 57/17*