

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

T23SR6W



from which

A fir, 14 ins. diam., bears S. 73° E., 93 lks. dist.,  
mkd.  $\frac{1}{4}$  S26 BT.


A fir, 6 ins. diam., bears S. 86° W., 41 lks. dist.,  
mkd.  $\frac{1}{4}$  S27 BT.

Ascend 35 ft. over broken E. slope.

56.865

Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground,  
with brass cap mkd.



from which

A fir, 18 ins. diam., bears N. 46° E., 10 lks. dist.,  
mkd. N 1/16 S26 BT.

A fir, 10 ins. diam., bears S. 66° W., 34 lks. dist.,  
mkd. N 1/16 S27 BT.

Descend 89 ft. over NE. slope.


60.87

Ravine, drains S. 80° E.; asc. 543 ft. over SW. slope.

75.82

Point for the cor. of secs. 22, 23, 26, and 27, at proportionate  
distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground,  
with brass cap mkd.



from which

A fir, 6 ins. diam., bears N. 35° E., 18 lks. dist.,  
mkd. T23S R6W S23 BT.

A fir, 7 ins. diam., bears S. 85 $\frac{1}{2}$ ° E., 38 lks. dist.,  
mkd. T23S R6W S26 BT.

A fir, 25 ins. diam., bears S. 29° W., 19 lks. dist.,  
mkd. T23S R6W S27 BT.

A fir, 9 ins. diam., bears N. 56° W., 10 lks. dist.,  
mkd. T23S R6W S22 BT.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and  
cedar. Undergrowth, salal, poison oak, vine maple, chinquapin,  
madrone, and alder.

From the cor. of secs. 23, 24, 25, and 26.

S. 88°59' W., bet. secs. 23 and 26.