

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

Descend 110 ft. over W. slope.

17.00 Spur, slopes N. 35° W.; desc. 79 ft. over NW. slope.

20.37 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 23}{S\ 26}$
1957

from which

A fir, 9 ins. diam., bears N. 29° E., 9 lks. dist.,
mkd. E 1/16 S23 BT.

A fir, 10 ins. diam., bears S. 26° E., 56 lks. dist.,
mkd. E 1/16 S26 BT.

Descend 77 ft. over NW. slope.

28.60 Creek, 5 lks. wide, course S. 5° W.; asc. 461 ft. over SE. slope, changing to S. slope.

40.74 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T23SR6W
 $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$
1957

from which

A madrone, 8 ins. diam., bears N. 65° E., 39 lks. dist.,
mkd. $\frac{1}{4}$ S23 BT.

A madrone, 6 ins. diam., bears S. 61° W., 54 lks. dist.,
mkd. $\frac{1}{4}$ S26 BT.

Ascend 58 ft. over S. slope.

49.18 Ridge, bears S. 55° E. and N. 55° W.; asc. 15 ft. over broken SE. slope.

60.81 Ravine, drains S. 30° E.; asc. 11 ft. over NE. slope.

61.11 Point for the W 1/16 sec. cor. of secs. 23 and 26.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 23}{S\ 26}$
1957

from which

A fir, 8 ins. diam., bears S. 3° E., 42 lks. dist.,
mkd. W 1/16 S26 BT.

A fir, 22 ins. diam., bears N. 46° W., 22 lks. dist.,
mkd. W 1/16 S23 BT.

Ascend 416 ft. over steep NE. slope.

79.00 Spur, slopes S. 45° E.; desc. 35 ft. over SW. slope.

81.48 The cor. of secs. 22, 23, 26, and 27.