

## Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

N. 1°49' W., bet. secs. 10 and 11.

Descend 82 ft. over NE. slope.

9.65 Creek, 1 lk. wide, course N. 50° E.; asc. 50 ft. over SE. slope.

13.15 Spur, slopes E.; desc. 21 ft. over NE. slope.

14.60 Ravine, drains S. 70° E.; asc. 71 ft. over SE. slope.


17.05 Spur, slopes N. 60° E.; desc. 246 ft. over NW. slope, changing to N. slope.

36.88 The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, determined at record bearing and distance to one of the original bearing trees:

A fir, 48 ins. diam., bears N. 80° E., 34 lks. dist.,  
mkd.  $\frac{1}{4}$  S BT.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.



from which

A fir, 24 ins. diam., bears S. 32° E., 112 lks. dist.,  
mkd.  $\frac{1}{4}$  S11 BT.

A fir, 30 ins. diam., bears N. 8° W., 75 lks. dist.,  
mkd.  $\frac{1}{4}$  S10 BT.

N. 0°04' E., beginning new measurement.

Descend 185 ft. over N. slope.

12.40 Creek, 10 lks. wide, course W., curving N.; asc. 225 ft. over SW. slope.

24.00 Ravine, course S. 10° W.; asc. 243 ft. over S. slope.

30.55 Spur, slopes S. 70° W.; desc. 166 ft. over NW. slope.

34.55 Ravine, course N. 50° W.; asc. 26 ft. over SW. slope.

41.34 Spur, slopes N. 70° W.; desc. 332 ft. over N. slope, changing to NW. slope.

49.28 The cor. of secs. 2, 3, 10, and 11, the badly weathered remains of old stake, 30 ins. long, 3 ins. sq., firmly set, no legible scribe marks.

from which

A fir, 50 ins. diam., bears S. 80° E., 33 lks. dist.,  
mkd. T23S R6W S11 BT under 60 years of overgrowth.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.