

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

T23SR6W
 $\frac{S}{S10} \frac{S}{S11}$
 1943

from which

A cedar, 25 ins. diam., bears N. $31\frac{3}{4}^\circ$ E., 88 lks. dist.,
 mkd. T23S R6W S2 BT.

A fir, 50 ins. diam., bears S. 79° E., 27 lks. dist.,
 mkd. T23S R6W S11 BT.

A cedar, 7 ins. diam., bears S. 10° W., 66 lks. dist.,
 mkd. T23S R6W S10 BT.

A fir, 36 ins. diam., bears N. 45° W., 117 lks. dist.,
 mkd. T23S R6W S3 BT.

Land, mountainous. Soil, clay loam. Timber, fir, cedar, and hemlock. Undergrowth, salal, poison oak, salmonberry, and vine maple.

From the cor. of secs. 1, 2, 11, and 12.

N. $86^\circ 33'$ W., bet. secs. 2 and 11.

Over N. slope, through heavy timber and dense undergrowth.

2.00 Spur, slopes N. 20° W.; desc. 614 ft. over NW. slope.

23.75 Ravine, course N. 15° W.; asc. 342 ft. over NE. slope.

33.55 Spur, slopes N.; desc. 238 ft. over NW. slope.

39.10 Creek, 2 lks. wide, course N.; asc. 2 ft. over NE. slope.

39.14 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4} \frac{S}{S11} \frac{2}{11}$
 1943

from which

A fir, 16 ins. diam., bears N. 42° W., 19 lks. dist.,
 mkd. $\frac{1}{4}$ S2 BT.

A fir, 10 ins. diam., bears S. $12\frac{1}{2}^\circ$ E., 15 lks. dist.,
 mkd. $\frac{1}{4}$ S11 BT.

Ascend 282 ft. over NE. slope.

46.40 Spur, slopes N.; desc. 285 ft. over NW. slope.

52.80 Creek, 1 lk. wide, course N. 10° E.; asc. 199 ft. over NE. slope.

57.80 Spur, slopes N. 20° E.; desc. 355 ft. over NW. slope.

65.25 Creek, 3 lks. wide, course N. 10° E.; asc. 253 ft. over NE. slope.

72.30 Spur, slopes N.; desc. 269 ft. over NW. slope.

78.28 The cor. of secs. 2, 3, 10, and 11.