Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS	
	N. 14°11' E., bet. secs. 33 and 34.
	Ascend 372 ft. over E. slope, changing to SE. slope.
15.50	Spur, slopes E.; desc. 139 ft. over NE. slope, changing to E. slope.
28.75	Ravine, drains S. 60° E.; asc. 329 ft. over SW. slope.
33.16	Spur,ridge, bears N. 70° W. and S. 70° E.; desc. 237 ft. over NE. slope, changing to E. slope.
40.215	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T23SR6W $\frac{1}{4}$ S33 | S34 1957
	from which
	A fir, 14 ins. diam., bears N. 23° E., 23 lks. dist., mkd. $\frac{1}{4}$ S34 BT.
	A fir, 14 ins. diam., bears N. 21° W., 21 lks. dist., mkd. $\frac{1}{4}$ S33 BT.
	Ascend 6 ft. over E. slope.
43.37	Ravine, drains S. 80° E.; asc. 561 ft. over SW. slope.
55.73	Spur ridge, bears S. 63° E. and N. 63° W.; desc. 372 ft. over NE. slope.
64.43	Ravine, drains S. 70° E.; asc. 468 ft. over SW. slope.
77.35	Spur, slopes S. 80° E.; desc. 163 ft. over N. slope.
80.43	Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T23SR6W S28 | S27 S33 | S34 1957
	from which
	A fir, 18 ins. diam., bears N. 69° E., 21 lks. dist., mkd. T23S R6W S27 BT.
	A fir, 6 ins. diam., bears S. 72° E., 35 lks. dist., mkd. T23S R6W S34 BT.
	A fir, 12 ins. diam., bears S. 24° W., 91 lks. dist., mkd. T23S R6W S33 BT.
	A fir, 8 ins. diam., bears N. 44° W., 36 lks. dist., mkd. T23S R6W S28 BT.
	Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, poison oak, salal, vine maple, salmonberry, alder, and chinquapin.