


Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS
40.17

Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 9 ins. diam., bears S. $77\frac{1}{2}^\circ$ E., 24 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

A fir, 9 ins. diam., bears S. 83° W., 102 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

Along E. slope.

41.00 Ravine, drains S. 80° E.; asc. 80 ft. over SE. slope.


45.00 Spur, slopes E.; desc. 9 ft. over NE. slope.

48.60 Ravine, drains S. 80° E.; asc. 55 ft. over SE. slope.

54.00 Ridge, bears N. 15° E. and S. 15° W.; desc. 45 ft. over broken W. slope.

80.34 Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A fir, 32 ins. diam., bears N. 34° E., 32 lks. dist., mkd. T23S R6W S22 BT.

A fir, 38 ins. diam., bears S. 67° E., 58 lks. dist., mkd. T23S R6W S27 BT.

A fir, 20 ins. diam., bears S. $88\frac{1}{2}^\circ$ W., 92 lks. dist., mkd. T23S R6W S28 BT.

A fir, 28 ins. diam., bears N. 17° W., 42 lks. dist., mkd. T23S R6W S21 BT.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, poison oak, salal, vine maple, madrone, and bracken fern.

From the cor. of secs. 22, 23, 26, and 27.

N. $88^\circ 44'$ W., bet. secs. 22 and 27.

Ascend 108 ft. over SW. slope, changing to S. slope.

17.00 Ridge, bears N. 60° E. and S. 60° W.; desc. 335 ft. over NW. slope.