

# County Surveyor's Record, Douglas County, Oregon

12880

## Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS	
66.65	Road, unimproved, 20 lks. wide, bears S. 20° E. and S. 40° W.; asc. 7 ft. over S. slope.
66.80	Ridge, bears E. and W.; desc. 418 ft. over NW. slope.
81.55	Creek, 15 lks. wide, course N. 65° E.; asc. 11 ft. over SE. slope.
82.36	Road, unimproved, 20 lks. wide, bears N. 65° E. and S. 65° W.; asc. 104 ft. over SE. slope.
84.80	The standard cor. of secs. 3 and 4, on the N. bdy. of the Tp.  Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, vine maple, salmonberry, poison oak, alder, laurel, and madrone.
From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp. N. 20°15' E., bet. secs. 32 and 33.  Ascend 213 ft. over SE. slope.	
7.49	Ridge, bears S. 40° E. and N. 40° W.; desc. 41 ft. along E. slope.
9.87	Swale, drains S. 35° E.; asc. 141 ft. over S. slope.
19.67	Spur, slopes SW.; asc. 100 ft. along W. slope.
32.55	Ridge, bears E. and W., road, 15 lks. wide, unimproved, bears E. and W.; desc. 292 ft. over N. slope, changing to NW. slope.
42.905	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
<div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 5px;">T23SR6W</div> <div style="margin-bottom: 5px;">↑</div> <div style="margin-bottom: 5px;">S32   S33</div> <div style="margin-bottom: 5px;">↓</div> <div style="margin-bottom: 5px;">1957</div> </div>	
from which	
A fir, 8 ins. diam., bears S. 9°45' E., 29 lks. dist., mkd. $\frac{1}{4}$ S33 BT.	
A fir, 15 ins. diam., bears N. 83°30' W., 33 lks. dist., mkd. $\frac{1}{4}$ S32 BT.	
Descend 130 ft. over NW. slope.	
50.52	Bottom of steep descent, edge bears NE. and SW.; asc. 6 ft. along W. slope.
56.52	Spur, slopes W.; desc. 333 ft. over NW. slope.
70.61	Creek, 5 lks. wide, course N. 70° W.; asc. 118 ft. over SW. slope.
75.04	Spur, slopes S. 65° W.; desc. 170 ft. along W. slope.
79.94	Bottom of descent; asc. 30 ft. over slight W. slope.
85.81	The cor. of secs. 28, 29, 32, and 33, determined at record distance from three of the original bearing trees: