

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

from which

A hemlock, 8 ins. diam., bears S. $16\frac{1}{2}^\circ$ E., 26 lks. dist.,
mkd. S 1/16 S9 BT.


Descend 12 ft. over NE. slope.

23.40 Creek, 5 lks. wide, course N. 55° W.; asc. 29 ft. over SW. slope,
changing to W. slope.

31.68 Creek, 1 lk. wide, course S. 57° W.; asc. 115 ft. over SE. slope,
changing to S. slope.

36.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate
distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground,
with brass cap mkd.



from which

A chinquapin, 12 ins. diam., bears S. 70° E., 43 lks. dist.,
mkd. $\frac{1}{4}$ S9 BT.

A fir, 10 ins. diam., bears S. 48° W., 89 lks. dist.,
mkd. $\frac{1}{4}$ S8 BT.

Ascend 61 ft. over S. slope.

51.31 Top of ascent on NW. slope; desc. 178 ft. over NW. slope.

55.63 Creek, 3 lks. wide, course S. 80° W.; asc. 280 ft. over SE. slope,
changing to E. slope.

66.72 Ridge, bears S. 34° W. and N. 10° E.; asc. 26 ft. along E. slope.


72.04 The cor. of secs. 4, 5, 8, and 9, determined at record bearing and
distance from an original bearing tree:

A fir, 24 ins. diam., bears S. 20° E., 16 lks. dist.,
mkd. BT.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 12 ins. in the
ground, and in a mound of stone, 8 ft. base, to top, with brass
cap mkd.

*FD. OK 2/93
BY HOFFME
C.S. 63/149*



from which

A cedar, 16 ins. diam., bears N. 33° E., 53 lks. dist.,
mkd. T23S R6W S4 BT.

A cedar, 12 ins. diam., bears S. 12° E., 88 lks. dist.,
mkd. T23S R6W S9 BT.

A cedar, 24 ins. diam., bears S. 42° W., 68 lks. dist.,
mkd. T23S R6W S8 BT.